


## 8MP ColorHunter with Wise-ISP Fixed Eyeball Network Camera IPC3628LE-ADF28(40)K-WP



## Features

- High quality image with 8 MP, 1/1.8" CMOS sensor and F1.0 large aperture lens
- 8 MP (3840 × 2160)@20 fps; 5 MP (3072 × 1728)@30/25 fps; 4 MP (2560 × 1440)@30/25 fps; 1080P (1920 × 1080)@30/25 fps
- Ultra 265, H.265, H.264, MJPEG
- ColorHunter with Wise-ISP technology ensures 24-hour full-color images
- 120 dB true WDR technology enables clear image in strong light scene
- Supports 9:16 corridor mode
- Built-in mic
- White light, up to 30 m (98.4 ft.) warm light distance
- MicroSD, up to 512 GB
- IP67 protection
- Supports PoE power supply
- 3-axis


## Specifications

| Model                              | IPC3628LE-ADF28K-WP                                                                                                                                                                                                                                                                                                                                                                  | IPC3628LE-ADF40K-WP |
|------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------|
| Camera                             |                                                                                                                                                                                                                                                                                                                                                                                      |                     |
| Max Resolution                     | 8 MP                                                                                                                                                                                                                                                                                                                                                                                 |                     |
| Sensor                             | 1/1.8" CMOS                                                                                                                                                                                                                                                                                                                                                                          |                     |
| Min. Illumination                  | Color: 0.0003 Lux (F1.0, AGC ON)                                                                                                                                                                                                                                                                                                                                                     |                     |
| Shutter                            | Auto/Manual, 1 ~ 1/100000s                                                                                                                                                                                                                                                                                                                                                           |                     |
| Adjustment Angle                   | Pan: 0° to 360°, Tilt: 0° to 90°, Rotate: 0° to 360°                                                                                                                                                                                                                                                                                                                                 |                     |
| S/N                                | >52 dB                                                                                                                                                                                                                                                                                                                                                                               |                     |
| WDR                                | 120 dB                                                                                                                                                                                                                                                                                                                                                                               |                     |
| Lens                               |                                                                                                                                                                                                                                                                                                                                                                                      |                     |
| Focal Length                       | 2.8 mm                                                                                                                                                                                                                                                                                                                                                                               | 4.0 mm              |
| Iris Type                          | Fixed                                                                                                                                                                                                                                                                                                                                                                                |                     |
| Iris                               | F1.0                                                                                                                                                                                                                                                                                                                                                                                 |                     |
| Field of View (H)                  | 111.0°                                                                                                                                                                                                                                                                                                                                                                               | 94.2°               |
| Field of View (V)                  | 63.0°                                                                                                                                                                                                                                                                                                                                                                                | 51.0°               |
| Field of View (D)                  | 131.0°                                                                                                                                                                                                                                                                                                                                                                               | 111.7°              |
| Lens Type                          | Fixed                                                                                                                                                                                                                                                                                                                                                                                |                     |
| DORI                               |                                                                                                                                                                                                                                                                                                                                                                                      |                     |
| DORI Distance (Lens)               | 2.8 mm                                                                                                                                                                                                                                                                                                                                                                               | 4 mm                |
| DORI Distance (Detect)             | 63.0 m (206.7 ft.)                                                                                                                                                                                                                                                                                                                                                                   | 90.0 m (295.3 ft.)  |
| DORI Distance (Observe)            | 25.2 m (82.7 ft.)                                                                                                                                                                                                                                                                                                                                                                    | 36.0 m (118.1 ft.)  |
| DORI Distance (Recognize)          | 12.6 m (41.3 ft.)                                                                                                                                                                                                                                                                                                                                                                    | 18.0 m (59.1 ft.)   |
| DORI Distance (Identify)           | 6.3 m (20.7 ft.)                                                                                                                                                                                                                                                                                                                                                                     | 9.0 m (29.5 ft.)    |
| Illuminator                        |                                                                                                                                                                                                                                                                                                                                                                                      |                     |
| Supplemental Light                 | Warm light                                                                                                                                                                                                                                                                                                                                                                           |                     |
| Illumination Distance (Warm Light) | 30 m (98.4 ft.)                                                                                                                                                                                                                                                                                                                                                                      |                     |
| Light On/Off Control               | Auto/Manual                                                                                                                                                                                                                                                                                                                                                                          |                     |
| Video                              |                                                                                                                                                                                                                                                                                                                                                                                      |                     |
| Video Compression                  | Ultra 265, H.265, H.264, MJPEG                                                                                                                                                                                                                                                                                                                                                       |                     |
| H.264 Code Profile                 | Baseline profile, Main profile, High profile                                                                                                                                                                                                                                                                                                                                         |                     |
| Frame Rate                         | Main Stream: 8 MP (3840 × 2160), max. 20 fps; 5 MP (3072 × 1728), max. 30 fps; 4 MP (2560 × 1440), max. 30 fps; 1080P (1920 × 1080), max. 30 fps; 720P (1280 × 720), max. 30 fps;<br>Sub Stream: 1080P (1920 × 1080), max. 30 fps; 720P (1280 × 720), max. 30 fps; D1 (720 × 576), max. 30 fps; 640 × 360, max. 30 fps; 2CIF (704 × 288), max. 30 fps; CIF (352 × 288), max. 30 fps; |                     |
| Video Bit Rate                     | 128 Kbps to 6144 Kbps                                                                                                                                                                                                                                                                                                                                                                |                     |
| U-code                             | Support                                                                                                                                                                                                                                                                                                                                                                              |                     |
| OSD                                | Up to 4 OSDs                                                                                                                                                                                                                                                                                                                                                                         |                     |
| Privacy Mask                       | Up to 4 areas                                                                                                                                                                                                                                                                                                                                                                        |                     |
| ROI                                | Support                                                                                                                                                                                                                                                                                                                                                                              |                     |
| Video Stream                       | Dual streams                                                                                                                                                                                                                                                                                                                                                                         |                     |

| Image                             |                                                                                                                                                                                                            |
|-----------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| White Balance                     | Auto, Outdoor, Fine tune, Sodium lamp, Locked, Auto2                                                                                                                                                       |
| Digital Noise Reduction           | 2D/3D DNR                                                                                                                                                                                                  |
| Smart Illumination                | Support                                                                                                                                                                                                    |
| Flip                              | Normal, Flip vertical, Flip horizontal, 180°, 90° Clockwise, 90° Anti-clockwise                                                                                                                            |
| Dewarping                         | N/A                                                                                                                                                                                                        |
| HLC                               | Support                                                                                                                                                                                                    |
| BLC                               | Support                                                                                                                                                                                                    |
| Defog                             | Digital defog                                                                                                                                                                                              |
| Image Stabilization               | N/A                                                                                                                                                                                                        |
| Events                            |                                                                                                                                                                                                            |
| Basic Detection                   | Motion detection, Ultra motion detection, Tampering alarm, Audio detection                                                                                                                                 |
| General Function                  | Watermark, IP address filtering, Access policy, ARP protection, RTSP authentication, User authentication, HTTP authentication                                                                              |
| Intelligent                       |                                                                                                                                                                                                            |
| Smart Intrusion Prevention (Lite) | Intrusion, crossline detection (both detection are based on human body and vehicle detection)                                                                                                              |
| Audio                             |                                                                                                                                                                                                            |
| Audio Compression                 | G.711U, G.711A                                                                                                                                                                                             |
| Audio Bitrate                     | 64 Kbps                                                                                                                                                                                                    |
| Two-way Audio                     | N/A                                                                                                                                                                                                        |
| Suppression                       | Support                                                                                                                                                                                                    |
| Sampling Rate                     | 8 kHz                                                                                                                                                                                                      |
| Storage                           |                                                                                                                                                                                                            |
| Edge Storage                      | MicroSD, up to 512 GB                                                                                                                                                                                      |
| Network Storage                   | ANR, NAS (NFS)                                                                                                                                                                                             |
| Network                           |                                                                                                                                                                                                            |
| Protocols                         | IPv4, IPv6, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP, SSL/TLS                                                        |
| Compatible Integration            | ONVIF (Profile S, Profile G, Profile T), API, SDK                                                                                                                                                          |
| User/Host                         | Up to 32 users, 2 user levels: administrator and common user                                                                                                                                               |
| Security                          | Password Protection, Strong Password, HTTPS Encryption, Export Operation Logs, Basic and Digest Authentication for RTSP, Digest Authentication for HTTP, TLS 1.2, WSSE and Digest Authentication for ONVIF |
| Client                            | EZStation, APP                                                                                                                                                                                             |
| Web Browser                       | Plug-in required live view: IE 10+, Chrome 45+, Firefox 52+, Edge 79+, Plug-in free live view: Chrome 57+, Firefox 58+, Edge 16+                                                                           |
| Interface                         |                                                                                                                                                                                                            |
| Audio I/O                         | N/A                                                                                                                                                                                                        |
| Alarm I/O                         | N/A                                                                                                                                                                                                        |
| Serial Port                       | N/A                                                                                                                                                                                                        |
| Built-in Mic                      | Support                                                                                                                                                                                                    |
| Built-in Speaker                  | N/A                                                                                                                                                                                                        |

|                     |                                                                                                                                                  |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------|
| WIFI                | N/A                                                                                                                                              |
| Network             | 1 × RJ45 10 M/100 M Base-TX Ethernet                                                                                                             |
| Video Output        | N/A                                                                                                                                              |
| Certification       |                                                                                                                                                  |
| EMC                 | CE-EMC (EN 55032, EN 61000-3-3, EN IEC 61000-3-2, EN 55035)<br>FCC (FCC 47 CFR part15 B)                                                         |
| Safety              | CE LVD (EN 62368-1)<br>UL/CUL (UL 62368-1, CAN/CSA C22.2 No. 62368-1)                                                                            |
| Environment         | CE-RoHS (2011/65/EU;(EU)2015/863); WEEE (2012/19/EU);                                                                                            |
| Protection          | IP67 (IEC 60529)                                                                                                                                 |
| General             |                                                                                                                                                  |
| Power               | DC 12 V±25%, PoE (IEEE 802.3af)                                                                                                                  |
| Power Consumption   | Max. 3.9 W                                                                                                                                       |
| Power Interface     | Ø5.5 mm coaxial power plug                                                                                                                       |
| Dimensions          | Ø118 mm × 106 mm (Ø4.6" × 4.2") (Ø × H)                                                                                                          |
| Weight              | 0.48 kg (1.06 lb.)                                                                                                                               |
| Material            | Metal + Plastic                                                                                                                                  |
| Working Environment | -30 °C to 60 °C (-22 °F to 140 °F), Humidity: ≤ 95% RH (non-condensing)                                                                          |
| Storage Environment | -30 °C to 60 °C (-22 °F to 140 °F), Humidity: ≤ 95% RH (non-condensing)                                                                          |
| Surge Protection    | 4 KV                                                                                                                                             |
| Reset Button        | Support                                                                                                                                          |
| Web Client Language | 13 Languages: English, Simplified Chinese, Polish, German, Russian, French, Korean, Dutch, Czech, Portuguese, Spanish, Spanish (Europe), Italian |

## Dimensions



## Accessories

### TR-JB03-I-IN

Junction Box for Plastic Turret  
Camera(Support wiring from behind)



### TR-SE24-A-IN

Dome Pendant Mounting Pole 500mm



### TR-SE24-IN

Dome Pendant Mounting Pole 200mm



### TR-CM24-IN

Dome Pendant Mounting Bracket(Indoor)



### TR-A01-IN

NPT 3/4" Waterproof Cable Gland



### TR-JB07/WM03-G-IN-V2

Wall Mounting Assembling Bracket For 32  
Fix-dome&Mini Fix-dome&Plastic Turret  
Camera



TR-WM03-D-IN-V2

Wall Mounting Bracket for 32

Fix-dome&Mini Fix-dome&Plastic Turret  
Camera



TR-UC08-C-V2

Bullet&Dome Corner Mounting Bracket



TR-UP06-C-IN-V2

Pole Mounting Bracket for Bullet Junction  
Box Only



**Zhejiang Uniview Technologies Co., Ltd.**



<http://www.uniview.com>



[overseasbusiness@uniview.com](mailto:overseasbusiness@uniview.com); [globalsupport@uniview.com](mailto:globalsupport@uniview.com)



No. 369, Xietong Road, Xixing Sub-district, Binjiang District, Hangzhou City, 310051, Zhejiang Province, China  
(Zhejiang) Pilot Free Trade Zone, China



©2023-2025 Zhejiang Uniview Technologies Co., Ltd. All rights reserved.

\*Product specifications and availability are subject to change without notice.

\*Despite our best efforts, technical or typographical errors may exist in this document.

Uniview cannot be held responsible for any such errors and reserves the right to change the contents of this document without prior notice.