MARCH networks
A Delta Group Company

March Networks™ CloudSight Cameras at-a-Glance

Choose your camera, boost your security. Below, explore the powerful CS+ Series with pro-grade analytics. Flip the page for the flexible, no-fuss CS Series—smart, simple, and reliable. Find your perfect fit in seconds.

	CS12+ 360° DOME	CS5+ DOME	CS5+ ATM
Series	**CS+**	**CS+**	**CS+**
Resolution	12MP	5MP	5MP
Image Sensor	1/2.3" CMOS	1/2.8" CMOS	1/2.7" CMOS
Lens Type	Fixed	Zoom	Fixed
Focal Length	f = 1.22 mm	f = 2.7~13.5 mm	f = 3.7 mm
F-number	F2.0	F1.4~F2.8	F2.5
Field of View (horiz./vert./diag.)	180°/ 180°/ 180°	95°-30°/ 70°-23°/ 128°-38°	93°/ 48°/ 117°
IR Illuminators	20 m	30 m	—
Audio	One-way (built-in microphone)	Two-way (External microphone Input)	One-way (built-in microphone)
Pre-installed SD Card	*	*	*
Ingress and Impact Rating	IP66/IK10	IP66/IP67/IK10	NA
Dimensions	D x H Ø 150 x 68.2 mm (Ø 5.9 x 2.69 in)	D x H Ø 155 x 103 mm (Ø 6.1 x 4.06 in)	L x W x H 105 x 84 x 30 mm (4.13 x 3.31 x 1.18 in)
Weight	701 g (1.55 lb)	900 g (2.0 lb)	190 g (0.42 lb)
Power	12 Vdc 1.75 A 37-57 Vdc 0.57-0.37 A (PoE 802.3at, Class 4)	12 Vdc 1.92 A 24 Vac 1.4 A 42.5-57 Vdc 0.53-0.4 A (PoE 802.3at, Class 4)	8-36 Vdc 1.1-0.24 A 37-57 Vdc 0.23-0.15 A (PoE 802.3af, Class 0)
Power Consumption	**IR On:** max. 22.5 W **IR Off:** max. 9.55 W	12 Vdc max. 13.8 W 24 Vac max. 15.5 W PoE max. 17 W	Max. 8.5 W
Operating Temperature	-40 °C to +50 °C (-40 °F to +122 °F)	-40 °C to +50 °C (-40 °F to +122 °F) – **IR On** -30 °C to +50 °C (-22 °F to +122 °F) – **IR Off**	-10 °C to +50 °C (+14 °F to +122 °F)
Humidity	90% RH, non-condensing	10-90% RH, non-condensing	90% RH, non-condensing
User Connections	Ethernet RJ45 10Base-T / 100Base-TX	Ethernet RJ45 10Base-T / 100Base-TX	Ethernet RJ45 10Base-T / 100Base-TX
WDR	WDR Pro	WDR Pro	WDR Pro
Video Analytics	**Real time alerting:** object removal, line-crossing, loitering, intrusion, abandoned object, blocked exit, scene search **Deep Search:** attribute search for people or vehicles, profile search, re-search		**Real time alerting:** line-crossing, loitering, intrusion, scene search **Deep Search:** attribute search for people or vehicles, profile search, re-search
Regulatory Model	C5001A	C4501A	C5601A
Part Number (days storage)	41943-101 (30 days) 41943-103 (90 days)	41942-101 (30 days) 41942-103 (90 days)	42932-101 (30 days) 42932-103 (90 days)

*Local Storage – Includes SD card with choice of 30-day or 90-day storage. Refer to the part number section to select your preferred storage capacity.

Scan the QR code to access the camera mounting solution guide.

March Networks™ CloudSight Cameras at-a-Glance

	CS5 INDOOR DOME	CS5 DOME	CS2 DOME
Series	**CS**	**CS**	**CS**
Resolution	5MP	5MP	2MP
Image Sensor	1/2.7" CMOS	1/2.7" CMOS	1/3.1" CMOS
Lens Type	Zoom	Fixed	Fixed
Focal Length	f = 2.8~10 mm	f = 2.8 mm	f = 2.8 mm
F-number	F1.8~F2.74	F2.0	F2.0
Field of View (horiz./vert./diag.)	95°~41°/ 69°~31°/ 127°~51°	103°/ 76°/ 134°	116°/ 65°/ 140°
IR Illuminators	30 m	30 m	30 m
Audio	One-way (built-in microphone)	One-way (built-in microphone)	One-way (built-in microphone)
Pre-installed SD Card	*	*	*
Ingress and Impact Rating	Indoor	IP66/IK10	IP66/IK10
Dimensions	D x H Ø 130 x 95 mm (Ø 5.12 x 3.74 in)	D x H Ø 129 x 94 mm (Ø 5.08 x 3.70 in)	D x H Ø 110 x 85 mm (Ø 4.33 x 3.34 in)
Weight	355 g (0.78 lb)	605 g (1.33 lb)	465 g (1.03 lb)
Power	37-57 Vdc 0.33-0.21 A (PoE 802.3af, Class 0)	37-57 Vdc 0.33-0.21 A (PoE 802.3af, Class 0)	12 Vdc 0.43 A 37-57 Vdc 0.16-0.11 A (PoE 802.3at, Class 4)
Power Consumption	**IR On:** max. 9.7 W **IR Off:** max. 7.3 W	**IR On:** max. 8.55 W **IR Off:** max. 6.15 W	**IR On** 12 Vdc max 5.1 W PoE max 6.49 W **IR Off** 12 Vdc max 3.4 W PoE max 4 W
Operating Temperature	-10 °C to +45 °C (+14 °F to +113 °F)	-40 °C to +50 °C (-40 °F to +122 °F)	-30 °C to +55 °C (-22 °F to +131 °F)
Humidity	90% RH, non-condensing	98% RH, non-condensing	95% RH, non-condensing
User Connections	Ethernet RJ45 10Base-T / 100Base-TX	Ethernet RJ45 10Base-T / 100Base-TX	Ethernet RJ45 10Base-T / 100Base-TX
WDR	WDR Pro	WDR Pro	WDR Enhanced
Video Analytics	**Real time alerting:** object removal, line-crossing, loitering, intrusion, abandoned object, blocked exit, scene search		
Regulatory Model	C5101A	C5201A	C4401A
Part Number (days storage)	41944-101 (30 days) 41944-103 (90 days)	41945-101 (30 days) 41945-103 (90 days)	41946-101 (30 days) 41946-103 (90 days)

*Local Storage – Includes SD card with choice of 30-day or 90-day storage. Refer to the part number section to select your preferred storage capacity.

Scan the QR code to access the camera mounting solution guide.

North America 1 800 563 5564
Latin America . . . . . +5255 5259 9511
Europe . . . . . +39 0362 17935
Asia . . . . . +65 6818 0963
Australia and New Zealand . . . . . +61 1300 089 419
Middle East and Africa . . . . . +971 4 399 5525

© 2025 March Networks. All rights reserved. Information in this document is subject to change without notice. MARCH NETWORKS, March Networks Command, March Networks Searchlight, March Networks RideSafe, and the MARCH NETWORKS logo are trademarks of March Networks Corporation. All other trademarks are the property of their respective owners. 060-3506-00-G

marchnetworks.com

MARCH networks
A Delta Group Company