

### SPCE80TW

8", white housing, 70V, each

### SPCE80TB

8", black housing, 70V, each

### SPCE60W

6.5", white housing, 8 Ohms, pair

### SPCE60B

6.5", black housing, 8 Ohms, pair

### SPCE60TW

6.5", white housing, 70V, pair

### SPCE60TB

6.5", black housing, 70V, pair

### SPCE50W

5.25", white housing, 8 Ohms, pair

### SPCE50B

5.25", black housing, 8 Ohms, pair

### SPCE50TW

5.25", white housing, 70V, pair

### SPCE50TB

5.25", black housing, 70V, pair



## Features

Contractor Elite is far from your common speaker line. Though designed with commercial applications in mind, these speakers are built with high-performance materials and features you'd find in high-end residential installations. The Contractor Elite Outdoor speaker line provides amazing sound, stylish looks, and easy installations – all for an amazing price.

- Great sound at an affordable price
- IP66 compliant, weather resistant
- Aluminum grille for extended use in outdoor environments
- "T" models come with a selectable 70V transformer
- 5 year warranty against manufacturing defects
- NDAA Compliant\*



| Speaker Specifications                     | (8" Models)                                   | (6.5" Models)                                   | (5.25" Models)                                     |
|--------------------------------------------|-----------------------------------------------|-------------------------------------------------|----------------------------------------------------|
| RMS Output Power                           | 100W                                          | 60W                                             | 40W                                                |
| Max Output Power                           | 140W                                          | 120W                                            | 80W                                                |
| Sensitivity (1W/1M)                        | 87dB                                          | 88dB                                            | 84dB                                               |
| Maximum SPL (Pmax/1M)                      | 108dB                                         | 102dB                                           | 100dB                                              |
| Impedance                                  | 8 Ohms                                        | 8 Ohms                                          | 8 Ohms                                             |
| Frequency Response Range                   | 65Hz - 20kHz                                  | 85Hz - 20kHz                                    | 90Hz - 20kHz                                       |
| Driver                                     | 8" polypropylene woofer, 1" silk dome tweeter | 6.5" polypropylene woofer, 1" silk dome tweeter | 5.25" polypropylene woofer, .75" silk dome tweeter |
| Transformer Settings (for "T" Models only) | 70V (100W, 50W, 25W, 12.5W, 8 Ohms)           | 70V (50W, 25W, 12.5W, 6W, 3W, 8 Ohms)           | 70V (40W, 20W, 10W, 5W, 2.5W, 8 Ohms)              |

## Operating Specifications

|                         |                               |                                 |                               |
|-------------------------|-------------------------------|---------------------------------|-------------------------------|
| Dimensions              | 9.8" (L) x 7" (D) x 15.6" (H) | 7.9" (L) x 6.6" (D) x 12.6" (H) | 7" (L) x 5.5" (D) x 11.3" (H) |
| Speaker Grille Material | Aluminum                      | Aluminum                        | Aluminum                      |

**NDAA**  
COMPLIANT

\* Products are in compliance with NDAA Section 889 Part B Guidelines



close-up image of transformer and wire terminals