

# Datasheet

## A22K - 2 Door/4 Reader IP Controller

### Product Description

The ATRIUM A22K two door IP controller works perfectly with the most popular Wiegand card readers or with the embedded KRYPTO high-security solution, providing the best of both worlds in access control.

KRYPTO is the easiest solution to manage DESFire® EV2/EV3 smart credentials on the market making worries of card cloning a thing of the past. The auto-restore of encryption keys upon power failure ensures an effortless system start up and management.

Additionally, the A22K can easily be converted to an Elevator Controller (A22KEC), Schlage Door Handle Controller (ADH2K), or Aperio Door Handle Controller (A2PK) as needed. ATRIUM's efficiency will simplify your life.

### Key Features

- Supports 2 doors & 4 readers (read in/read out with KRYPTO readers)
- End-to-end AES encryption (when combined with KRYPTO readers)
- Embedded secure HTTPS (SSL/TLS) web server
- Includes free ATRIUM software & updates
- Up to 500 doors, 10,000 users & cards
- Pre-assembled plug-in power supply
- App to unlock doors with a phone (when combined with KRYPTO mobile-ready readers)

**KRYPTO** HIGH SECURITY SOLUTION **ATRIUM** ACCESS CONTROL



System Capacity	
Users / Cards	10,000 / 10,000
Access Levels	1,000
Holidays	100
Schedules (100 time periods each)	250
Event Buffer	25,000
Floor levels	256
Areas	10



Certification



Certification



DEEE



Certification



-4°F to 158°F  
(-20°C to 70°C)

## Communication

**On-board Ethernet:** 10/100 Base-T, Auto Sensing, 100 m (300 ft)  
**Local BUS:** RS485 communication for expanders

## Input Specifications

**Reader/Keypad Ports (Wiegand or RS485):** 2  
**Multi-purpose inputs:** 2 (4 using zonedoubling)

## Output Specifications

**Lock outputs:** 2 (750 mA @12 VDC/each)  
**Relay outputs:** 2 Form C relays, 5A @250 VAC, 7A @125 VAC, 7A @30 VDC  
**Reader Outputs (Wiegand):** 6 x 50 mA Open collector output  
**Multi-purpose outputs:** 2 x 50 mA Open collector output

## On-board Protection (all fuseless and auto-resume)




**LK1 & LK2** 12 VDC @ 750 mA  
**Auxiliary outputs:** 1A (12 VDC) fuseless protection  
**Battery:** Against reversal, short, current limited/monitored

## Electrical Specifications

**Power input:** 120 VAC to 240 VAC, 50/60Hz  
**Power output:** 24 VDC, 2.5 A  
**AC Terminal Fuse:** 250 VA, 2.5 A. Time Lag, Slow Blow  
**Power Loss Indicator:** Yes (DC IN)  
**Battery backup:** One 12 VDC, 7 Ah, gel cell batteries

## Recommended Wiring

Equipment	Wire Type	Size	Maximum Length
Card reader and Wiegand keypad	4 to 8 conductors, stranded, shielded (foil), drain conductor. For example: Alpha 5196, 5198, 5386, 5388, Belden 9553	22AWG (0.64mm) to 18AWG (1.02mm)	150m (500ft.)
Zone input	2 conductors, copper 22AWG (0.64mm)	22AWG (0.64mm)	600m (2000ft.)
Door strike	2 conductors, solid copper 18AWG (1.02mm)	18AWG (1.02mm)	150m (500ft.)
Power Supply	3 conductors, solid copper 18AWG (1.02mm)	14AWG (1.63mm)*	8m (25ft.)
Ethernet	CAT 5/5e	-	100m (300ft)
RS485 bus, Star or Daisy Chain (no BIAS/EOL required)	CAT 5/5e or 4 pairs	24AWG (0.51mm)	1220m (4000ft.)
	4 conductors, copper	26AWG (0.40mm) to 18AWG (1.02 mm)	



All the information contained within this document (pictures, drawings, features, dimensions, specifications), could be perceptibly different and can be changed without prior notice. Published: 09 May 2025. CDVI\_A22K\_DS\_01\_EN-FR\_LETTER\_C

# Datasheet

## NANOPB - Mini Proximity Reader

### Product Description

The NANO from CDVI is a mini and compact proximity card reader.

As with the other readers from the range (STAR, SOLAR and SOLARK), the NANO gives an anytime status of the door through multi-colored LED's.

These access control readers have a high performance read range and are easy to mount.



### Key Features

- Award winning innovative design
- Reads CDVI cards only
- PCB Sealed in epoxy
- Audible and visual feedback
- Multicolored LED



Certification



Certification



DEEE



Certification



IP53



-13°F to 158°F  
(-25°C to 70°C)


All the information contained within this document (pictures, drawings, features, dimensions, specifications), could be perceptibly different and can be changed without prior notice. Published: 07 August 2023. CDVI\_NANOPB\_DS\_01\_EN-FR\_LETTER\_C

## Product Specifications

<b>Material:</b>	Polycarbonate
<b>Mounting:</b>	Surface
<b>Technology:</b>	125 kHz
<b>Security level:</b>	Standard
<b>Protocol:</b>	26, 30 or 44 bits
<b>Read range:</b>	Up to 2" (5 cm)
<b>Weight:</b>	1.4 oz, 40 g

## Electrical Specifications

<b>Power input:</b>	12 VDC
<b>Consumption:</b>	100 mA



## Accessories



**ISO25**

Printable ISO Card



**CS25**

Clamshell Card



**BTAG25**

Blue Proximity Key Tag

All the information contained within this document (pictures, drawings, features, dimensions, specifications), could be perceptibly different and can be changed without prior notice. Published: 07 August 2023. CDVI\_NANOPB\_DS\_01\_EN-FR\_LETTER\_C

## Datasheet

### KTAG25 - Black Key Ring Tag

#### Product Description

The KTAG25 is a black PVC fob with a handy metal keyring. It contains a 125 kHz RFID chip, this affordable RFID proximity solution is ideal for any standard access control projects.

CDVI offers a variety of access control credentials with different technologies (125 kHz proximity or MIFARE®). You'll find the ideal credentials to meet the needs of your installation. You can also customize our CDVI cards and tags with your own company logo (minimum order of 1,000 units).



#### Key Features

- CDVI 26-bit encoding (125 kHz)
- Sequential decimal number printed on each tag
- Available in packs of 25

 Certification

 DEEE

 Certification

## Product Specifications

<b>Material:</b>	PVC
<b>Technology:</b>	CDVI 26-bit encoding
<b>Frequency:</b>	125 kHz
<b>Security level:</b>	Standard
<b>Weight:</b>	0.2 oz, 8 g



## Also available in these technologies



**KTAGH25**  
HID-compatible 125 kHz  
Key Ring Tag



**KTAGM25**  
MIFARE® Classic (13.56 MHz)  
Key Ring Tag

All the information contained within this document (pictures, drawings, features, dimensions, specifications), could be perceptibly different and can be changed without prior notice. Published: 21 June 2023. CDVI\_KTAG25\_DS\_01\_EN+FR\_LETTER\_C


# Datasheet

## CS25 - Clamshell Card

### Product Description

The CS25 is a standard clamshell card. It contains a 125 kHz proximity technology RFID chip. This affordable RFID proximity solution is ideal for any standard access control projects.

CDVI offers a variety of access control credentials with different technologies (125 kHz proximity or MIFARE®). You'll find the ideal credentials to meet the needs of your installation. You can also customize our CDVI cards and tags with your own company logo (minimum order of 1,000 units).



### Key Features

- CDVI 26-bit encoding
- Sequential decimal number printed on each card
- Available in packs of 25


 Certification

 DEEE

 Certification

## Product Specifications

<b>Material:</b>	PVC
<b>Technology:</b>	CDVI 26-bit encoding
<b>Frequency:</b>	125 kHz
<b>Security level:</b>	Standard
<b>Weight:</b>	0.2 oz, 8 g



## Also available in these technologies



**CSH25**

HID-compatible 26-bit 125 kHz  
Clamshell Card



**CSM**

MIFARE® Classic 1K 13.56 MHz  
Clamshell Card



**CSDT**

Dual-Tech CDVI 125 kHz &  
DESFire® EV2 Clamshell Card

## Datasheet

### DISCTAG25 - Sticker Credential

#### Product Description

The DISCTAG25 is a small PVC sticker credential. It contains a 125 kHz RFID chip. This affordable RFID proximity solution is ideal for any standard access control projects.

CDVI offers a variety of access control credentials with different technologies (125 kHz proximity or MIFARE®). You'll find the ideal credentials to meet the needs of your installation. You can also customize our CDVI cards and tags with your own company logo (minimum order of 1,000 units).

*\*Contact with wireless phone chargers may damage RFID credentials.*



#### Key Features

- CDVI 26-bit encoding (125 kHz)
- Sequential decimal number printed on each sticker
- Available in packs of 25

 Certification

 DEEE

 Certification

## Product Specifications

<b>Material:</b>	PVC
<b>Technology:</b>	CDVI 26-bit encoding
<b>Frequency:</b>	125 kHz
<b>Security level:</b>	Standard
<b>Weight:</b>	0.3 oz, 1 g



1.2" dia. (30 mm dia.)

## Also available in these technologies



**DISCTAGH25**  
HID-compatible (125 kHz)  
Sticker Credential



**DISCTAGM**  
MIFARE® Classic (13.56 MHz)  
Sticker Credential