



ALTV1224C

### **Overview**

ALTV1224C AC/DC Dual Output Power Supply is designed to provide both 12VDC and 24VAC outputs where a combination of both AC and DC outputs are required.

### **Specifications**

#### ***Input:***

- 115VAC 50/60 Hz, 1.52 amp.

#### ***Output:***

- Sixteen (16) individually fused outputs.
  - Eight (8) fuse protected outputs @ 12VDC.
  - Eight (8) fuse protected outputs @ 24VAC.
- 7 amp total output current.
  - 3.5 amp supply current @ 12VDC.
  - 3.5 amp supply current @ 24VAC.
- Output fuses are rated @ 3.5 amp/250VAC.
- Main fuses are rated at 5 amp/250VAC.
- Filtered and electronically regulated outputs (DC outputs).
- Surge suppression (AC outputs).

#### ***Electrical:***

- Operating temperature: -20° C to 49° C ambient.

#### ***Electrical (cont'd):***

- BTU/Hr.:
  - 12VDC: 21.49 BTU/Hr.
  - 24VAC: 42.97 BTU/Hr.
- System AC input VA requirement: 174.8VA.

#### ***Features:***

- AC/DC power LED indicators.
- Power ON/OFF switch.
- Unit maintains camera synchronization.
- Ease of installation saves time & eliminates costly labor.

#### ***Mechanical:***

- NEMA1 enclosure.
- Enclosure Dimensions (H x W x D approx.): 15.5" x 12" x 4.5" (393.7mm x 304.8mm x 114.3mm)
- Product weight (approx.): 17.75 lbs. (8.05 kg).
- Shipping weight (approx.): 19.05 lbs. (8.64 kg).

**Enclosure Dimensions (H x W x D approximate):**  
 15.5" x 12" x 4.5" (393.7mm x 304.8mm x 114.3mm)

