



ALTV1224DC1

Overview

ALTV1224DC1 provides 12VDC or 24VDC distributed via sixteen (16) fuse protected outputs for powering CCTV Cameras, heaters and other video accessories.

Specifications***Input:***

- Input 115VAC, 50/60 Hz, 1.45 amp.

Output:

- Sixteen (16) fuse protected outputs.
- 12VDC or 24VDC.
- 4 amp total continuous supply current
(0.25 amp per device, 3.5 amp max.).
- Outputs are rated @ 3.5 amp.
- Filtered and electronically regulated outputs.

Electrical:

- Operating temperature: 0° C to 49° C ambient.
- 24.57 or 49.14 BTU/Hr.
- System AC input VA requirement: 166.75VA.

Features:

- AC input and DC output LED indicators.
- Power ON/OFF switch.
- Unit maintains camera synchronization.
- Ease of installation saves time and eliminates costly labor.

Mechanical:

- NEMA1 enclosure.
- Enclosure Dimensions (H x W x D approx.):
13.5" x 13" x 3.25" (342.9mm x 330.2mm x 82.55mm)
- Product weight (approx.): 7.9 lbs. (3.58 kg).
- Shipping weight (approx.): 8.8 lbs. (3.99 kg).

Enclosure Dimensions (H x W x D approximate):
 13.5" x 13" x 3.25" (342.9mm x 330.2mm x 82.55mm)

