



ALTV2416600UL, ALTV2416600ULCB UL Listed AC CCTV Power Supply

Rev. DSALTV2416600UL -B13F

Overview



- These Altronix AC Wall Mount CCTV Power Supplies provide 24VAC or 28VAC distributed via sixteen (16) fuse or Class 2 Rated PTC protected power limited outputs for powering CCTV Cameras, heaters and other video accessories.

ALTV2416600UL

- Sixteen (16) fuse protected outputs.
- Outputs are rated @ 3.5 amp.

ALTV2416600UL3

ALTV2416600UL w/3-wire
Line Cord.

ALTV2416600ULCB

- Sixteen (16) Class 2 Rated PTC protected power limited outputs.
- Outputs are rated @ 2.5 amp.

ALTV2416600UCB3

ALTV2416600ULCB w/3-wire
Line Cord.

Specifications

- Input 115VAC, 50/60Hz, 5.4 amp.
- 24VAC @ 25 amp (600VA) or 28VAC @ 20 amp (560VA) supply current.
- Main fuse rated @ 15 amp/32V.
- Illuminated power disconnect circuit breaker with manual reset.
- Surge suppression.
- AC power LEDs.
- Spare fuse(s) provided (all models w/primary and/or secondary fuses).
- Unit maintains camera synchronization.
- Ease of installation saves time and eliminates costly labor.

- Product weight:
 - ALTV2416600UL: 22.8 lbs.
 - ALTV2416600UL3: 23.1 lbs.
 - ALTV2416600ULCB: 22.8 lbs.
 - ALTV2416600UCB3: 23.1 lbs.
- Shipping weight:
 - ALTV2416600UL: 23.7 lbs.
 - ALTV2416600UL3: 24.0 lbs.
 - ALTV2416600ULCB: 23.7 lbs.
 - ALTV2416600UCB3: 24.0 lbs.

Agency Approvals



UL Listed for Commercial CCTV Equipment (UL 2044).



European Conformity



CUL Listed - CSA Standard C22.2 No.1-98, Audio, Video and Similar Equipment.

Enclosure Dimensions

13"H x 13.5"W x 3.5"D

