



Overview

- These Altronix AC Wall Mount CCTV Power Supplies provide 24VAC or 28VAC distributed via eight (8) fuse or Class 2 Rated PTC protected power limited outputs for powering CCTV Cameras, heaters and other video accessories.

ALTV248175UL

- Eight (8) fuse protected outputs.
- Outputs are rated 3.5 amp.

ALTV248175UL3

ALTV248175UL w/3-wire Line Cord.

ALTV248175ULCB

- Eight (8) Class 2 Rated PTC protected power limited outputs.
- Outputs are rated @ 2.5 amp.

ALTV248175ULCB3

ALTV248175ULCB w/3-wire Line Cord.

Specifications

- Input 115VAC, 50/60Hz, 1.73 amp.
- 24VAC @ 7 amp (170VA) or 28VAC @ 6.25 amp (175VA) supply current.
- Main fuse rated @ 10 amp/250V.
- Illuminated power disconnect circuit breaker with manual reset.
- Surge suppression.
- AC power LED.
- Spare fuse(s) provided (all models w/primary and/or secondary fuses).
- Unit maintains camera synchronization.
- Ease of installation saves time and eliminates costly labor.
- Product weight:
 - ALTV248175UL: 10.9 lbs.
 - ALTV248175UL3: 11.2 lbs.
 - ALTV248175ULCB: 10.9 lbs.
 - ALTV248175ULCB3: 11.2 lbs.
- Shipping weight:
 - ALTV248175UL: 11.7 lbs.
 - ALTV248175UL3: 12.0 lbs.
 - ALTV248175ULCB: 11.7 lbs.
 - ALTV248175ULCB3: 12.0 lbs.

Agency Approvals



UL Listed for Commercial CCTV Equipment (UL 2044).



CUL Listed - CSA Standard C22.2 No.1-98, Audio, Video and Similar Equipment.



European Conformity

Enclosure Dimensions

12.25"H x 7.75"W x 4.5"D

