



ALTV248300UL, ALTV248300ULCB UL Listed AC CCTV Power Supply

Rev. DSALTV248300UL - B16F

Overview



- These Altronix AC Wall Mount CCTV Power Supplies provide 24VAC or 28VAC distributed via eight (8) fuse or Class 2 Rated PTC protected power limited outputs for powering CCTV Cameras, heaters and other video accessories.

ALTV248300UL

- Eight (8) fuse protected outputs.
- Outputs are rated @ 3.5 amp.

ALTV248300UL3

ALTV248300UL w/3-wire Line Cord.

ALTV248300ULCB

- Eight (8) Class 2 Rated PTC protected power limited outputs.
- Outputs are rated @ 2.5 amp.

ALTV248300ULCB3

ALTV248300ULCB w/3-wire Line Cord.

Specifications

- Input 115VAC, 50/60Hz, 2.7 amp.
 - 24VAC @ 12.5 amp (300VA) or 28VAC @ 10 amp (280VA) supply current.
 - Main fuse rated @ 15 amp/32V.
 - Illuminated power disconnect circuit breaker with manual reset.
 - Surge suppression.
 - AC power LED.
 - Spare fuse(s) provided (all models w/primary and/or secondary fuses).
 - Unit maintains camera synchronization.
 - Ease of installation saves time and eliminates costly labor.
- Product weight:
 - ALTV248300UL: 11.3 lbs.
 - ALTV248300UL3: 11.6 lbs.
 - ALTV248300ULCB: 11.3 lbs.
 - ALTV248300ULCB3: 11.6 lbs.
 - Shipping weight:
 - ALTV248300UL: 12.1 lbs.
 - ALTV248300UL3: 12.4 lbs.
 - ALTV248300ULCB: 12.1 lbs.
 - ALTV248300ULCB3: 12.4 lbs.

Agency Approvals



UL Listed for Commercial CCTV Equipment (UL 2044).



European Conformity



CUL Listed - CSA Standard C22.2 No.1-98, Audio, Video and Similar Equipment.

Enclosure Dimensions

12.25"H x 7.75"W x 4.5"D

