



ALTV248UL, ALTV248ULCB UL Listed AC CCTV Power Supply

Rev. DSALTV248UL - B21F

Overview



- These Altronix AC Wall Mount CCTV Power Supplies provide 24VAC or 28VAC distributed via eight (8) fuse or Class 2 Rated PTC protected power limited outputs for powering CCTV Cameras, heaters and other video accessories.

ALTV248UL

- Eight (8) fuse protected outputs.
- Outputs are rated @ 3.5 amp.

ALTV248UL3

ALTV248UL w/3-wire Line Cord.

ALTV248ULCB

- Eight (8) Class 2 Rated PTC protected power limited outputs.
- Outputs are rated @ 2.5 amp.

ALTV248ULCB3

ALTV248ULCB w/3-wire Line Cord.

Specifications

- Input 115VAC, 50/60Hz, .9 amp.
- 24VAC @ 3.5 amp (85VA) or 28VAC @ 3 amp (85VA) supply current.
- Main fuse rated @ 5 amp/250V.
- Power ON/OFF switch.
- Surge suppression.
- AC power LED.
- Spare fuse(s) provided (all models w/primary and/or secondary fuses).
- Unit maintains camera synchronization.
- Ease of installation saves time and eliminates costly labor.
- Product weight:
 - ALTV248UL: 6.5 lbs.
 - ALTV248UL3: 6.8 lbs.
 - ALTV248ULCB: 6.4 lbs.
 - ALTV248ULCB3: 6.7 lbs.
- Shipping weight:
 - ALTV248UL: 7.0 lbs.
 - ALTV248UL3: 7.3 lbs.
 - ALTV248ULCB: 7.0 lbs.
 - ALTV248ULCB3: 7.3 lbs.

Agency Approvals



UL Listed for Commercial CCTV Equipment (UL 2044).



Canadian Standard Association



CUL Listed - CSA Standard C22.2 No.1-98, Audio, Video and Similar Equipment.



European Conformity

Enclosure Dimensions

8.5"H x 7.5"W x 3.5"D

