

Mid-Range 5.8 GHz Wireless Link Point to Point Access Device

AP2PMD

Mid Range Wireless Link


Features

- 2-in-1 Wireless bridge and PoE switch
- 5*10/100Mbps RJ45 port
- Supports DC 12-52V or POE 48-56V input
- Supports RS-485 signal control
- Supports IEEE 802.11 a/n protocol
- Wireless speed up to 300Mbps
- 5.8G wireless bridge transmission distance can reach 3000 meters
- Professional outdoor shell design, IP55 dustproof and waterproof protection level
- Dual PoE Output



Specifications

Model	Specification
Port	5*10/100Mbps RJ45 Port
	1*DC Interface (DC input voltage is 48-52V)
Wireless Bridge	IEEE802.11n, IEEE802.11a, IEEE802.3u
	IEEE802.3af, IEEE802.3at
Power	Power Input Voltage:DC 12-52V / POE 48-56V
	Maximum Power of the Single Port :25W (Requires 60W power supply)
802.11a	6-24Mbps, 36-48Mbps, 54Mbps
802.11ac	Up to 144 Mbps
	Up to 300 Mbps
	Up to 867 Mbps
Management	WEP Management
	SNMP MIB
	Telnet
	Serial
MAC Address Control	No, WEP Encryption 64/128bits, WPA,WPA2,802.1x
Operating Temperature	-22F - 140F
Storage Temperature	-58F - 170F
Humidity (non-condensed)	≤ 95% (non-condensed)
Dimensions	Size: 8.98in x 5.31in x 1.69in
	Weight: 1.0lbs



Products are in compliance with NDAA Section 889 Part B Guidelines. ONVIF® is a trademark of Onvif, Inc. Chrome® and Firefox® use Java™, which requires an initial internet connection. Apple® and the Apple logo® are trademarks of Apple Inc., registered in the U.S. and other countries. App Store® is a service mark of Apple Inc. Android™ is a trademark of Google LLC. Google Play® and the Google Play logo® are trademarks of Google LLC. Amazon® is a trademark of Amazon.com, Inc. or its affiliates, used under license. Speco Technologies® is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Revised 7/11/25