

## DESCRIPTION


The AP-8-RM is a rack mounted four- zone audio base station designed to interface with a DVR, VCR or other recording devices that accept line level input. The AP-8-RM Audio Base Station contains a built-in 3" speaker and volume control for producing live audio and audio playback. Has mute switch to mute audio from being heard at the speaker.



AP-8-RM Audio Base Station



AD-1 Power Supply



DUAL RCA Cable

## CONTENTS

AP-8-RM (UL) Listed Audio Base Station (Rack Mounted)

AD-1 (UL) Listed AC ADAPTER

Dual RCA Cable

## APPLICATION

The AP-8-RM is designed for numerous applications such as:

- Convenience Stores
- Sleep Disorder Centers
- Fast Food Restaurants
- Speech Therapy Labs
- Booking Rooms
- Cashier Booths
- Interrogation Rooms
- Casino use in:
  - soft count rooms
  - detention centers
  - medical treatment rooms
- Car dealership sales contract rooms
- Child Abuse Interviews
- cash cages

### WIRING REQUIREMENTS

2 Conductor **shielded** cable, 22 gauge with a 24 gauge drain wire.

**NOTE:** Unshielded cable is not satisfactory for audio systems.

West Penn 452 or equivalent



## FEATURES

- Audio output (RCA) to DVR, VCR
- 3" speaker for monitoring live audio and playback from a DVR or VCR
- 3.5 mm headphone jack for private listening
- Mute switch to mute audio from being heard at the speaker
- Overload LED to indicate short in wiring connections
- 8 Line level microphone outputs

## SPECIFICATIONS

Monitor power output	1W @ 8Ω
Audio output impedance	1KΩ
Audio input impedance	10kΩ
Freq. response	100 Hz to 10kHz
Headphone impedance	8 to 600Ω
Current Drain	200mA
Power input	12 Vdc, 500mA
Dimensions	19"L x 3 1/2"W x 8 5/8"D
Weight	3 lbs
Shipping Weight	4 lbs