



Proximity Reader and Keypad

APCR620L

Mullion proximity reader with Bluetooth® and keypad

Features

- Up to 15 ft. of read range
- Keypad with contactless proximity and mobile credential access support
- Digital Radio Frequency Identification (RFID) platform
- Supports both sector and card serial number (CSN) reads
- Offers the option of mobile access credentials loaded on Bluetooth® Low Energy (BLE) enabled smartphones or contactless proximity module
- IP67 compliant, weather resistant
- Tamper resistant
- Lifetime warranty

Technical Specifications

Models	Mullion-Mount Mobile-Ready Proximity Reader and Keypad
Technology	Proximity and Bluetooth® Low Energy (BLE)
Frequency	125 kHz (proximity) and 2.4 GHz (BLE)
Mounting	Mullions, including metal door and window frames, as well as flat surfaces
Dimensions	1.78" W × 6.1" H × 0.91" D (45mm × 155mm × 23mm)
OEM Label Area	0.9" W × 0.35" H (22.86mm × 8.89mm) with corner radius of 0.06" (1.5mm)
Certifications	FCC, ICC, CE, UL Standard 294, ULC 60839-11-12
IP Code3	IP67
Voltage4	+8 to 14 VDC
Current Draw	0 mA typical, 90 mA peak @ 12 VDC
Read Range5	Physical credentials: up to 4" (102mm)
Mobile Credentials:	Up to 15 feet (4.6 m)6
Cabling7	24 AWG minimum, multiconductor stranded with an overall foil shield
Interface	Wiegand (26-bit and custom formats), ABA Track II magnetic stripe (clock and data) or OSDP8
Operating Temperature	-31° F to 150° F (-35° C to +66° C)
Operating Humidity	0% to 90% relative humidity
Color Options	A black snap-on cover included standard
Audio Tone	Beeper included standard
Indoor & Outdoor Installation	Electronics sealed in weather- and tamper-resistant epoxy potting
Warranty	Limited lifetime warranty
LED	Four-state standard (red, green, amber, and off)
Keypad Output	Either Wiegand9 or OSDP8
Technologies Supported	Pyramid + certain HID® 125-kHz Proximity protocols + certain AWID® 125-kHz Proximity protocols10 Conect11 12 or Switch™ Tech13 ("Switch Keys") Mobile Access Credentials



Optional Accessories



ACMC2
Mobile Credential



APDT1
Proximity Disc Tag



APSM2
Proximity Card



APSI4
Proximity Card



APSK3
Proximity
Key Ring Tag



APSC1
Clamshell
Proximity Card



AWRT4
Long Range
Transmitters

NDAA
COMPLIANT



Products are in compliance with NDAA Section 889 Part B Guidelines. Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Android, Google Play and the Google Play logo are trademarks of Google Inc. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Revised 7/30/24

www.specotech.com

800.645.5516 • Fax: 631.957.9142 or 631.957.3880

speco
technologies