JOUROE FLECTRONICS

\mathbf{UROE} ASK-4 8 KIT #200 & ASK-4 KIT #300

AUDIO MONITORING SYSTEM

DESCRIPTION



MA-1 INTERFACE ADAPTER

ASK-4 KIT #200



VERIFACT A MICROPHONE

ASK-4 Kit #200 is a single zone audio monitoring system designed for direct connection to a CCTV Monitor with built-in amplifier and speaker. Model MA-1 Interface Adapter (located near the CCTV Monitor) receives the wiring from the Verifact A Microphone, supplies power and drives the audio signals into the "Audio In" port of the CCTV Monitor. The MA-1 also has RCA input/output jacks for recording and playback from a VCR/DVR. Audio playback is channeled through the TV Monitor.

KIT CONTENTS

ASK-4 KIT #200

- VERIFACT Model A Microphone
- Model MA-1 Interface Adapter
- Model AD-1 12Vdc power transformer
- Single RCA cable for connection to TV monitor
- Dual RCA cable for connection to recording device

APPLICATION

The ASK-4 Kit #200 and #300 can be used in situations such as:

- Convenience Stores
- Fast Food Restaurants
- Casino Soft Count Rooms
- Cashier Booths
 - ...Anywhere CCTV Cameras Are Installed

IMPORTANT NOTICE

When this equipment is used as part of an audio monitoring system, the law requires that the public be given notice of AUDIO MONITORING ON THE PREMISES. A decal notice is included with each microphone shipped.

Federal Law References: Federal Regulations, US Code, Title 18. Crime and Criminal Procedure, Sec 2510.

IF-1 with the state of the stat

IF-1 INTERFACE ADAPTER

ASK-4 KIT #300



VERIFACT A MICROPHONE

ASK-4 Kit #300 is a single zone audio monitoring system designed for direct connection to a VCR, DVR or computer sound card. Model IF-1 Interface Adapter (located near the recording device) receives the wiring from the Verifact A Microphone, supplies power and drives the audio signals into the recording device (VCR/DVR) or computer sound card.

KIT CONTENTS

ASK-4 KIT #300

- VERIFACT Model A Microphone
- Model IF-1 Interface Adapter
- Model AD-1 12Vdc power transformer
- Single RCA cable for connection to recording device
- 3.5mm stereo cable for connection to computer card

WIRING REQUIREMENTS (both kits)

2 Conductor shielded cable, 22 gauge with a 24 gauge drain wire (West Penn 452 or equiv.)

MICROPHONE DESCRIPTION

The Verifact A Microphone in both ASK-4 Kit #200 and #300 is an electret condenser type with pre-amp, omni-directional pattern and produces line level output. It can pick up normal sounds approximately 15' away all directions or within a 30' diameter circle. It is normally surface mounted to a ceiling but may also be installed to a wall or a flat surface.

SPECIFICATIONS (Microphone - Model A)

| oalanced |
|---------------|
| 15 kHz ± 1 dB |
| |
| Ω 000 |
| |
| ½"H |
| |