VIVOTEK
A Delta Group Company

AU-003



Technical Specifications

Product Information	
Rated Impedance	8 ohm
PoE Standard	IEEE 802.3af
Max. Power Consumption	15 W
Frequency Ranges	500-2 kHz +-10 dB 400-12 kHz +-20 dB
Max. Sound Pressure Level	113 dB
Microphone	50 Hz-20 kHz at 1 Pa, 50 cm distance, SPL 115 dB at 1 kHz

Network	
SIP Support	RFC 3261
Interface	WAN: RJ-45x1, 10/100Mbps Fast Ethernet port
Supported Protocols	DHCP, FTP, SIP, TFTP, ARP, HTTP, IPv4, NFS, NTP, ONVIF, RTCP, RTP, RTSP, TCP, UDP
Audio Codec	G.711 PCMA 8 kHz, G.711 PCMU 8 kHz, G.722 ADPCM 16 kHz, MP3 44.1 kHz, OPUS 48 kHz
Security	Password protection, IP address filtering, Digest authentication, firewall

VSS Integration	
Broadcasting	Supported
Automatic Trigger Audio Clips	Supported

VORTEX Integration	
Broadcasting	Supported
Automatic Trigger Audio Clips	Supported

General

Casing	ABS, IP66 water-proof
Power	PoE (Power over Ethernet, IEEE 802.3af) or DC 12-24V
Operating Temperature	-35°C ~ 60°C (-31°F ~ 140°F)
Dimensions	225 x 165 x 240 mm
Weight	1.3 kg
Certifications	CE, FCC, BSMI, VCCI

Data subject to change without notice. All right reserved. | sales@vivotek.com | www.vivotek.com | Ver. 20261004