

BRB-X1610E



BRB-X1610E

16CH BLAZE Appliance



Key Features

- Pre-installed BLAZE Client, Server and 16ch premium licenses
- Up to 150Mbps recording bandwidth
- 2 HDD bays (3.5"), up to 32TB
- RAID 1 support
- Hardened OS
- 2 x RJ-45 (1Gbps)
- NDAA compliant, UL listed, FCC certified

BRB-X1610E

16CH BLAZE Appliance



Specifications

System		
Video Management Software		BLAZE VMS
Licenses		16 x BLAZE Premium License
Available Channels		Up to 16 channels
Recording Rate		Up to 150Mbps
OS Drive Bays		eMMC 32GB
Data Drive Bays		SATA 2ea
Data Storage		Up to 32TB
RAID Support		RAID 1
Network Interface		2 x RJ-45 (1Gbps)
Memory		8GB DDR4
Operating System		Hardened OS
Decoding	Video Outputs	Duplicate: 1 x HDMI(4K), 1 x DP(4K), Extend: 1 x HDMI(FHD), 1 x DP(FHD)
	Resolution	Decoding Performance (H.264) - UHD Duplicate Mode: 6CH*8M@15fps, 14CH*2M@15fps, 16CH*640x360@7fps - FHD/FHD Extend Mode: (2CH+2CH)*8M@15fps, (6CH+6CH)*2M@15fps, (8CH+8CH)*640x360@7fps
USB Ports		Front 2 x USB 2.0 Rear 2 x USB 3.0
Audio	Output	1x Audio output
	Audio Communication	2-Way (Audio In: USB Mic)
Keyboard & Mouse		Keyboard, Mouse
Mechanical		
Form Factor		Box
Color / Material		Black / Metal
Dimensions (WxHxD)		14.57"(370mm) x 2.00"(50.7mm) x 12.60"(320mm)
Weight		5.95lbs (2.70Kg)
Electrical		
Power Input		100 ~ 240 VAC $\pm$ 10%, 50/60 Hz
Power Consumption		72W (245.66 BTU)

Environmental

Operating Temperature	32°F to 104°F(0°C to 40°C)
Operating Humidity	20% to 85% RH (non-condensing)


BRB-X1610E

16CH BLAZE Appliance



CAD

Unit: mm [inch]



© Hanwha Vision Co.,Ltd. All rights reserved.