



# BRS-P2H1SH3

BLAZE Recording Server (Windows Server OS)



## Key Features

2U BLAZE Recording Server, BLAZE pre-installed, up to 240TB raw (up to 200TB usable after disk formatting & RAID 5 configuration), 1200 Mbps recording B/W, 12 HDD Bay (3.5"), Intel Xeon 4410Y, 32GB RAM, Dual 480GB SSD OS drives (RAID 1), Windows Server 2022, Support RAID 0/1/5/6 + 8GB NV cache, mDP output, VGA output, 2 x 1GbE, 2 x 10GbE NICs, IPMI, Redundant 1100W power supplies, Keyboard and mouse included, Rail kit included

# BRS-P2H1SH3

BLAZE Recording Server (Windows Server OS)



## Specifications

| System                    |               |                                                             |
|---------------------------|---------------|-------------------------------------------------------------|
| Video Management Software |               | BLAZE VMS                                                   |
| Licenses                  |               | No License                                                  |
| Available Channels        |               | Up to 256 channels                                          |
| Recording Rate            |               | Up to 1200Mbps                                              |
| OS Drive Bays             |               | SSD 2 x 480GB RAID 1                                        |
| Data Drive Bays           |               | SATA 12ea                                                   |
| Data Storage              |               | Up to 240TB                                                 |
| RAID Support              |               | RAID 0, RAID 1, RAID 5, RAID 6, RAID 10                     |
| Network Interface         |               | 2 x RJ-45 (1Gbps), 2 x RJ-45 (10Gbps)                       |
| Processor                 |               | 1 x Intel Xeon 4410Y                                        |
| Memory                    |               | 32GB DDR5                                                   |
| Operating System          |               | Windows Server 2022                                         |
| IPMI                      |               | Supported                                                   |
| Decoding                  | Video Outputs | 1 x VGA, NVIDIA Quadro A400 4 x mDP, 1x mDP to HDMI adapter |
| USB Ports                 |               | Front: 1 x USB 2.0 Rear: 1 x USB 2.0, 1 x USB 3.0           |
| Other Ports               |               | Serial                                                      |
| Keyboard & Mouse          |               | Keyboard, Mouse                                             |
| Sliding Rail Kit          |               | Included, with Cable Management Arm                         |
| Security                  |               |                                                             |
| Security Certificate      |               | UL, NOM, RoHS, TUV, GS                                      |
| Mechanical                |               |                                                             |
| Form Factor               |               | 2U rack                                                     |
| Color / Material          |               | Black / Metal                                               |
| Dimensions (WxHxD)        |               | 18.97"(482mm) x 3.41"(86.8mm) x 30.39"(772.13mm)            |
| Weight                    |               | 53.3 lbs (25.1 kg)                                          |
| Electrical                |               |                                                             |
| Power Input               |               | 100 ~ 240 VAC $\pm$ 10%, 50/60 Hz                           |

---

**Electrical**

|                   |                            |
|-------------------|----------------------------|
| Power Supply      | 2 x 1100W 80 Plus Platinum |
| Power Consumption | 3000 Max BTU/hr            |

---

**Environmental**

|                       |                               |
|-----------------------|-------------------------------|
| Operating Temperature | 50°F to 95°F(10°C to 35°C)    |
| Storage Temperature   | -40°F to 149°F(-40°C to 65°C) |
| Operating Humidity    | 5% to 95% RH                  |