

Surface Mount Line Level Microphone

CAMMIC2 15" cable

Features

- Can be wall or ceiling mounted
- Designed for indoor spaces
- Ideal pickup range of 10 to 120 square feet
- Gain control to increase or reduce pick-up sensitivity
- High-fidelity, high sensitivity, high bandwidth, and low noise.
- Built-in high-speed voice processing with dynamic noise reduction.
- Built-in self-gain control AGC processing circuit which effectively minimizes speech signal distortion and attenuation.
- Built-in lightning protection with reverse polarity power protection and power protection module.
- Integrated professional audio pre-amplification processing circuit to directly drive active speakers, hard disk recordings, headphones, etc.
- Long-range audio signal transmission technology
- 2 year warranty
- NDAA Compliant*



Specifications

Range	10 - 120 ft. ²
Sensitivity	-43dB @ 1000 Hz
S/N	Max 65dB
Operating Voltage	9 - 12VDC, 25mA (max) (not included)
Dimensions	3.4" (W) x 1" (H)
Connection Mode	Red (power), white (RCA audio)
Sensitivity Adjustment	On board, accessed through cutout on back of unit

NDAA
COMPLIANT

*Products are in compliance with NDAA Section 889 Part B Guidelines

Optional Accessory



PSW5
12VDC
Power Supply