

4" 3-Way Indoor/Outdoor Wall-Mount Speaker with Transformer

DMS3TS

Black housing

DMS3TSW

White housing

Features

- Compact, full-range design
- Each speaker contains:
 - 4" Polypropylene woofer,
 - 2" Polypropylene midrange and
 - 1" Polypropylene dome tweeter
- Die-cast enclosure, complete with mounting bracket, speaker wire and mounting hardware
- Weather-resistant design
- 5 year warranty



Specifications

RMS Power	15W
Max Power.....	25W
Transformer Type	70/25V (selectable)
Transformer Power Taps	15W, 7.5W, 4W, 2W, 1W & 8 Ohms
Termination Type	Screw terminal
Sensitivity (1W/1M).....	86dB
Maximum SPL (Pmax/1m).....	97dB
Driver Impedance	8 Ohms
Magnet.....	10 oz. ferrite
Frequency Response Range...	110Hz ~ 20kHz
Dispersion @ 1000Hz	180° conical
Driver	4" polypropylene woofer, 2" mylar midrange, 1" mylar tweeter
Speaker Dimensions	4.5 (W) x 7.25" (H) x 4.375" (D)
Weight	4.2 lbs.
Material.....	Body: Aluminum Gille: Treated metal

NDAA
COMPLIANT

*Products are in compliance with NDAA Section 889 Part B Guidelines