

2.1MP/1080p indoor dome IP camera DWC-MD72Di28T



Summary

This MEGApix® IP camera provides 2.1MP/1080p resolution at real-time 30fps. The indoor dome camera includes a 2.8mm fixed lens and simultaneous H.265/H.264/MJPEG codec support and brings the capabilities of a robust camera in a small and discrete housing. All MEGApix® cameras are ONVIF conformant, assuring their successful integration with any open platform solution on the market.

Features

- 2.1MP/1080p 1/2.9" image sensor at real-time 30fps
- 2.8mm fixed lens
- Digital Wide Dynamic Range (D-WDR)
- Triple codecs (H.265, H.264, MJPEG) with simultaneous streaming
- 50' Smart IR™ with intelligent camera sync
- Smart DNR[™] 3D digital noise reduction
- True day/night mechanical IR cut filter
- Programmable privacy zones
- Auto gain control (AGC)
- Backlight compensation (BLC)
- Auto white balance (AWB)
- Motion detection
- · Web server built-in
- PoE class 2 and DC12V
- UL listed
- ONVIF conformant, profile S
- 5 year warranty

Accessories (Optional)



DWC-GPLT-W Converter plate for electronic gang box - white





4.13"

0.14

Specifications

A

Dimensions

unit: Inch (mm)

2.93 (74 P

2.1MP/1080p 1/2.9" CMOS 2001(H) X 1121(V)
0.25 lux (color)
0.0 lux (B/W)
2.8mm, F2.0
Fixed lens
109°
50ft range
Auto, manual, anti-flicker, slow shutter
1/15 ~ 1/32000
2X, 3X, 5X, 6X, 7.5X, 10X
Auto
Auto, day (color), night (B/W)
3D-DNR
D-WDR
16 programmable privacy masks
Yes
Yes
Notifications via e-mail and FTP server recording
RJ45 (10/100Base-T)
H.265, H.264, MJPEG
H.265: 2.1MP/1080p, 720p(main), CIF(sub) H.264: 2.1MP/1080p, 720p(main), CIF(sub) MJPEG: CIF
Up to 30fps at all resolutions
100Kbps ~ 10Mbps, multi-rate for preview and recording
Multi streaming CBR/VBR at H.264, H.265 (controllable frame rate and bandwidth)
Dual-stream at different rates and resolutions
IPv4, IPv6
TCP/IP, UDP, AutoIP, RTP(UDP/TCP), RTSP, NTP, HTTP, HTTPS, SSL, DNS, DDNS, DHCP, FTP, SMTP, ICMP, SNMPv1/v2/v3(MIB-2), ONVIF
HTTPS(SSL), IP filtering, 802.1x, digest authentication (ID/PW)
Yes
OS: Windows®, Mac® OS, Linux®
Browser: Internet Explorer®, Google Chrome®, Mozilla Firefox®, Safari®
DW Spectrum [®] IPVMS
-4°F ~ 122°F (-20°C ~ 50°C)
10-90% (non-condensing)
UL listed, CE, FCC, RoHS
DC 12V, PoE (IEEE 802.3af Class 2). (Adapter not included)
DC12V: max 3.8W PoE: max 5.5W
Plastic housing, polycarbonate dome
4.13" x 2.93" (105 x 74.6mm)
0.66lbs (0.3Kg)



Οηνιέ