















Resolution Intelligent Video Analytics

## Summary

This MEGApix® IVA™ IP camera is your gateway to powerful video analytics features. It is NDAA compliant and provides 2.1MP/1080p resolution at real-time 30fps. The MEGApix IVA cameras have a powerful engine to detect and classify people and vehicles in realtime. IVA+ license upgrade offers advanced Video Content Analysis detection capabilities. This camera includes a 2.8mm fixed lens, simultaneous H.265/H.264/MJPEG codec support and Star-Light Plus™ color in near-total darkness technology for quality video in any lighting condition. The weather-resistant vandal ball cameras are IP67 rated, eliminate IR reflections and offer easy angle adjustment for optimal image quality. All MEGApix® cameras are ONVIF conformant, assuring their successful integration with any open platform solution on the market.

#### **Features**

- 2.1MP/1080p 1/2.8" image sensor at real-time 30fps
- Star-Light Plus™ color in near-total darkness technology
- Intelligent Video Analytics (IVA)
- Extended Intelligent Video Analytics (IVA+ license required)
- Seamless integration and control of IVA rules with DW Spectrum® IPVMS
- Reduce false alarms
- Increase your recording storage with logic rules and smart recording
- · 2.8mm fixed lens
- True Wide Dynamic Range (WDR)
- Triple codecs (H.265, H.264, MJPEG) with simultaneous streaming
- 100' Smart IR™ with intelligent camera sync
- Vandal ball housing reduces IR reflection with true 90° tilting and 360° rotation
- Smart DNR™ 3D digital noise reduction
- True day/night mechanical IR cut filter
- Programmable privacy zones
- Auto gain control (AGC)
- Auto white balance (AWB)
- Motion detection
- PoE class 3 and DC12V
- **UL** listed
- NDAA compliant
- IP67 dust-tight and waterproof to 3 feet
- IK 10-rated impact-resistant
- 5 year warranty

#### Accessories (Optional)









DWC-VAWM Wall mount bracket



Onvif

### **Dimensions** Unit: Inch (mm)





# **Specifications**



AP/1080p 1/2.8" CMOS 5 (H) X 1109 (V) 5 lux (color) 1 lux (B/W)  mm, F2.0 ed lens 2 / 59° fft range  A license: intrusion, line crossing, counting line, loitering er, exit, tamper er, exit, tamper er, exit, tamper the license: object removed, tailgating, direction, stopped object, on manual, anti-flicker, slow shutter 5 - 1/32000 1/3,1/5,1/6,1/7.5, 1/10 100 101 102 103 104 105 105 105 105 105 105 105 105 105 105
5 (H) X 1109 (V) 5 lux (color) lux (B/W)  mm, F2.0 ed lens 2 / 59° fft range  A license: intrusion, line crossing, counting line, loitering er, exit, tamper  ++ license: object removed, tailgating, direction, stopped color, disappear, object left  to, manual, anti-flicker, slow shutter 1/32000 1/3,1/5,1/6,1/7.5, 1/10 to to, day (color), night (B/W)  -DNR  e WDR, 120dB programmable privacy masks
5 lux (color) -lux (B/W)  mm, F2.0 ed lens -2 / 59°  off range  A license: intrusion, line crossing, counting line, loitering er, exit, tamper  License: object removed, tailgating, direction, stopped ear, disappear, object left  co, manual, anti-flicker, slow shutter  5 - 1/32000  1/3,1/5,1/6,1/7.5, 1/10  100  101  102  103  104  105  105  106  107  107  108  109  109  109  109  109  109  109
mm, F2.0 ed lens 2 / 59°  off range  license: intrusion, line crossing, counting line, loitering er, exit, tamper er, exit, tamper  license: object removed, tailgating, direction, stopped pear, disappear, object left loo, manual, anti-flicker, slow shutter 6 - 1/32000 1/3,1/5,1/6,1/7.5, 1/10 1/0 1/0 1/0 1/0 1/0 1/0 1/0 1/0 1/0
mm, F2.0 ed lens 0 / 59° off range  I license: intrusion, line crossing, counting line, loitering er, exit, tamper  I license: object removed, tailgating, direction, stoppedear, disappear, object left  IO, manual, anti-flicker, slow shutter  5 - 1/32000  1/3,1/5,1/6,1/7.5, 1/10  IO
ed lens 2 / 59° Ift range  A license: intrusion, line crossing, counting line, loitering er, exit, tamper  L+ license: object removed, tailgating, direction, stopped ear, disappear, object left  Lo, manual, anti-flicker, slow shutter  - 1/32000  1/3,1/5,1/6,1/7.5, 1/10  LO  LO  LO  LO  LO  LO  LO  LO  LO  L
ed lens 2 / 59° Ift range  A license: intrusion, line crossing, counting line, loitering er, exit, tamper  L+ license: object removed, tailgating, direction, stopped ear, disappear, object left  Lo, manual, anti-flicker, slow shutter  - 1/32000  1/3,1/5,1/6,1/7.5, 1/10  LO  LO  LO  LO  LO  LO  LO  LO  LO  L
o/ 59°  Ift range  License: intrusion, line crossing, counting line, loitering er, exit, tamper  License: object removed, tailgating, direction, stopped page and disappear, object left  Lo, manual, anti-flicker, slow shutter  - 1/32000  1/3,1/5,1/6,1/7.5, 1/10  LO, day (color), night (B/W)  DDNR  e WDR, 120dB  programmable privacy masks
off range  It range  It license: intrusion, line crossing, counting line, loitering er, exit, tamper  It license: object removed, tailgating, direction, stopped object left  It is not manual, anti-flicker, slow shutter  It is 1/32000  I/3,1/5,1/6,1/7.5, 1/10  It is o, day (color), night (B/W)  IDNR  It when the work is the work of the work
k license: intrusion, line crossing, counting line, loitering er, exit, tamper  k+ license: object removed, tailgating, direction, stopped bear, disappear, object left  co, manual, anti-flicker, slow shutter  5 - 1/32000  1/3,1/5,1/6,1/7.5, 1/10  10  10  10  10  10  10  10  10  10
er, exit, tamper
to, manual, anti-flicker, slow shutter - 1/32000 1/3,1/5,1/6,1/7.5, 1/10 to to, day (color), night (B/W) -DNR e WDR, 120dB programmable privacy masks
is - 1/32000 1/3,1/5,1/6,1/7.5, 1/10 10 10 10 10 10 10 10 10 10 10 10 10 1
1/3,1/5,1/6,1/7.5, 1/10 to to, day (color), night (B/W) -DNR e WDR, 120dB programmable privacy masks
to, day (color), night (B/W)  DNR  e WDR, 120dB  programmable privacy masks
co, day (color), night (B/W) -DNR e WDR, 120dB programmable privacy masks
-DNR e WDR, 120dB orogrammable privacy masks
e WDR, 120dB orogrammable privacy masks
orogrammable privacy masks 6 6
5
3
tifications via e-mail and FTP server recording
45 (10/100Base-T)
65, H.264, MJPEG
65: 2.1MP/1080p, 720p, VGA, D1, CIF 64: 2.1MP/1080p, 720p, VGA, D1, CIF PEG: 1280x720, 800x600, VGA, 768x432, D1, CIF
to 30fps at all resolutions
OKbps ~ 10Mbps, multi-rate for preview and recording
lti streaming CBR/VBR at H.264, H.265 (controllable frame e and bandwidth)
al-stream at different rates and resolutions
4, IPv6
P/IP, UDP, AutoIP, RTP (UDP/TCP), RTSP, NTP, HTTP, TPS, SSL, DNS, DDNS, DHCP, FTP, SMTP, ICMP, MPV1/V2/V3 (MIB-2), ONVIF
TPS (TLS), IP filtering, 802.1x, digest authentication (ID/PW)
5
: Windows*, Mac* OS, Linux*
owser: IE®, Google Chrome®, Mozilla Firefox®, Safari® TE: Chrome browser is recommended for IVA ofiguration
/ Spectrum® IPVMS
F ~ 122°F (-20°C ~ 50°C)
90% (non-condensing)
7-rated , IK10 impact-resistant
listed, CE, FCC, RoHS
12V, PoE IEEE 802.3af Class 3. (Adapter not included)
12V: max 5.7W =: max 7.2W
minum vandal ball housing
· · · · · · · · · · · · · · · · · · ·
2" x 4.8" (125 x 122 mm) Sibs (0.8kg)





: sales@digital-watchdog.com



: www.digital-watchdog.com

