




HD over Coax[™]



4 Channels
120 Total fps



PathFinder[™]

5MP
Up to 5MP
Recording

4K
Ultra HD
Output

5 YEAR
Limited Warranty

Summary

VMAX[®] A1 Plus[™] DVRs support HD-Analog and HD-TVI signals up to 5MP and CVBS up to 960H. The DVRs offer a seamless upgrade to HD resolution for new ROI from existing coaxial infrastructure. The VMAX[®] A1 Plus[™] can record 1080p video at real-time 30fps. Up the Coax (UTC) remote configuration is available with all compatible cameras. The 4-channel DVR is available with up to 10TB of storage.

Features

- Universal HD over Coax[®] DVR records HD-Analog and HD-TVI and all analog up to 960H signals
- Advanced H.264 Linux[®] embedded DVR
- 4-channels, real-time 30fps recording up to 5MP
- Up to 5MP recording resolution at 40fps
- myDW[®] Cloud Management Services
- PathFinder[™] auto port forwarding
- C3[™] CMS and event server software up to 288Channels
- Event camera group recording
- Complete system analysis with real-time system and network status monitoring
- Mobile Application for iPhone[®], iPad[®], iPod[®], Android[®] Smart Phones and Tablets and Apple TV[®]
- Mac[®] compatible remote ACS software
- OSD and PTZ control via coax (UTC)
- Signal hybrid detects any camera at HD-Analog, HD-TVI and 960H automatically.
- Instant channel swap, no need to disconnect or reboot the DVR.
- Snapshot Notify[™]: programmable interval snapshot notifications
- 4K (3840 x 2160) True HD, VGA and Spot video outputs
- 2TB - 10TB storage options
- HDD calculation and auto-recording configuration
- Thumbnail search with hour and 5-minute previews
- 10-second jump buttons for playback and fast forward
- Event notifications via e-mail and C3[™] CMS and push notifications to mobile devices
- Multiplex - live, playback, recording, backup, network, configuration
- 4 audio input, 1 audio output
- 4 sensor input, 1 relay output
- Digital spot monitoring output at D1 resolution
- Simple and free DDNS service
- Push notifications via DW[®] VMAX[®] Plus[™] app
- Easy web-based client with multi-user access
- Help menu on major functions
- Auto and manual firmware upgrades
- 5 year limited warranty

Available Models

- DW-VA1P41T - 1TB, 4CH
- DW-VA1P42T - 2TB, 4CH
- DW-VA1P43T - 3TB, 4CH
- DW-VA1P44T - 4TB, 4CH
- DW-VA1P46T - 6TB, 4CH
- DW-VA1P48T - 8TB, 4CH
- DW-VA1P410T - 10TB, 4CH
- DW-VA1P4 - no local storage

Dimensions


Unit: Inch (mm)

1.77" (45mm)

9.84" (250mm)

9.52" (242mm)

1.88" (48mm)



Specifications

VIDEO			
Operating system	Embedded Linux [®]		
System	channel	4CH	
	Signals supported	Analog signal up to 960H, HD-Analog and HD-TVI up to 5MP	
Video-out	Monitor	True HD, VGA and Spot outputs	
	Framerate	120fps	
	Resolution	HDMI: 2560x1440, 3840x2160 (4K), 800x600, 1024x768, 1280x1024, 1920x1080 VGA: 800x600, 1024x768, 1280x1024, 1920x1080 Spot: D1	
	Screen mode	1 & 4	
Audio	Input	4 Inputs	
	Output	1 output	
	Codec	ADPCM	
Alarm	Alarm input	4 inputs	
	Alarm output	1 output	
Serial	1x RS485 for keyboard and PTZ control		
User interface	Graphical user interface (GUI), IR remote control, USB mouse		
PERFORMANCE			
Recording	Compression	H.264	
	Recording mode	Continuous, schedules, sensor-activated, motion detection, pre and post alarm, emergency, quick backup	
	Pre recording	0- 5sec	
	Post recording	0-5min	
	Recording rate	960x480/576 (960H):	120fps
		1280x720 (HD):	120fps
1920x1080 (HD):		120fps	
2560x1600 (4MP):		60fps	
Recording resolutions	2560x1944 (5MP):	40fps	
	352 x 240, 720 x 480, 960 x 480, 1280x720, 1920x1080, 2560x1600, 2560x1440, 2560x 1944		
Playback	Playback rate	960x480/576 (960H): 120fps 1280x720 (HD): 120fps 1920x1080 (HD): 120fps 2560x1600 (4MP): 60fps 2560x1944 (5MP): 40fps	
	Playback resolution	1, 4, 9 & 16 Ch at 1080P (up to 4K 3840x2160)	
	Fast forward functions	x1, x2, x4, x8, x16, x32	
	Playback functions	Intelli-search by time bar, calendar (date and time), event search and thumbnail search	
	Storage	HDD interface	1x SATA HDD
Max. internal storage		10TB	
HDD interface type		SATA	
Features	HDD health check	Temperature, S.M.A.R.T. with e-mail notifications	
	Camera color control	Via UTC	
	Digital zoom	Live and playback	
	Software upgrade	USB flash drive, network upgrade, FTP remote upgrade	
	Mobile client	Mobile app for Apple [®] & Android [®] smart phones & tablets	
NETWORK	LAN	Ethernet (1 x gigabit) 960x480/576 (960H): 120fps 1280x720 (HD): 120fps 1920x1080 (HD): 120fps 2560x1600 (4MP): 60fps 2560x1944 (5MP): 40fps	
	Streaming	Transmission speed live	
Access	Protocol	Fixed IP, DHCP, UPnP, DDNS	
	Web viewer	Live, playback and configuration up to 10 multiple connections	
Network features	Client monitoring software	Mac [®] (Apple [®] S/W), C3 [™] (CMS S/W), myDW [™] web portal and mobile app	
	Dual stream, separate local recording and network transmission	Network bandwidth control (25 Kbps - 1000 Mbps)	
	Time synchronization by NTP server ("pool.ntp.org")	Remote & E-mail notification, remote system reboot by IE, remote PTZ control	
	PathFinder [™] P2P service (auto port forwarding)		
Backup device	Local backup by USB and CMS over the network and FTP		
System recovery after power failure	Auto-reboot and journaling file system		
GENERAL			
Operating temperature and humidity	41°F - 104°F (5°C - 40°C), less than 80% (non-condensing)		
Certification	CE & FCC & KCC & WEEE, RoHS		
Power requirements	DC12V		
Power consumption	18W, 1.5A		
Dimension (W x D x H)	12.4" x 9.52" x 1.77" (315 x 242 x 45 mm) (1U)		
Weight	2.64 lbs (1.2kg)		
Warranty	5 year limited		