

HAC346D-VD4Z



FEATURES

5 MP Ultra-Low Light Camera

- 5 MP, 2560 × 1944 resolution
- Ultra-low light
- 130 dB true WDR, 3D DNR
- 2.7 mm to 13.5 mm varifocal lens, auto focus
- Smart IR, up to 60 m IR distance
- 4 in 1 video output (switchable TVI/AHD/CVI/CVBS)
- IP67

| | |
|--------------------------|---|
| Resolution | 2560 (H) × 1944 (V) |
| Min. Illumination | 0.003 Lux @ (F1.2, AGC ON), 0 Lux with IR |
| Frame Rate | TVI: 5MP@20fps, 4MP@25fps, 4MP@30fps, 2MP@25fps, 2MP@30fps AHD: 5MP@20fps, 4MP@25fps, 4MP@30fps CVI: 4MP@25fps, 4MP@30fps CVBS: PAL, NTSC |
| Shutter Time | 1/30 s to 1/50, 000 s |
| Lens | 2.7 mm to 13.5 mm motorized varifocal lens |
| Horizontal Field of View | 92.3° to 29.3° |
| Lens Mount | Φ 14 |
| Day & Night | ICR |
| WDR (Wide Dynamic Range) | ≥130 dB |
| Angle Adjustment | Pan: 0° to 360°; Tilt: 0° to 75°; Rotate: 0° to 360° |
| Image Mode | STD/HIGH-SAT |
| AGC | Yes |
| Day/Night Mode | Auto/Color/BW (Black and White) |

| | |
|-------------------------|--|
| White Balance | Auto/Manual |
| AE (Auto Exposure) Mode | WDR/BLC/Global |
| Privacy Mask | 4 programmable privacy masks |
| Motion Detection | 4 programmable motion areas |
| Noise Reduction | 3D DNR |
| Language | English |
| Function | Brightness, Sharpness, Mirror, Smart IR |
| Video Output | Switchable TVI/AHD/CVI/CVBS |
| Operating Conditions | -40 °C to 60 °C (-40 °F to 140 °F), humidity: 90% or less (non-condensing) |
| Power Supply | 12 VDC ± 20%, 24 VAC ± 20% |
| Power Consumption | Max. 10.5 W |
| Protection Level | IP67 |
| Material | Metal |
| IR Range | Up to 60 m |
| Communication | UTC-C |
| Dimensions | 123.86 mm × 134.3 mm × 110.24 mm (4.88" × 5.29" × 4.34") |
| Weight | Approx. 630 g (1.39 lb.) |
| Wall Mount | HTH-273ZJ-130-TRL |
| Pole Mount | HTH-275ZJ-SUS |
| Corner Mount | HTH-276ZJ-SUS |
| Junction Box | HTH-280ZJ-M |