

eBridge1CR
and eBridge1CT

Overview

The eBridge1CRT - IP over Coax transceiver and receiver kit is designed to enable fast 10/100Base-T Ethernet digital communication over coax cable. These plug and play units facilitate system upgrades from analog to IP cameras/devices utilizing existing legacy Coax and eliminating the costs and labor associated with installing new network cabling. In addition data transmission is extended to 2,000' (over five times the 100m/328' Ethernet maximum length), eliminating the need for repeaters. eBridge units will transmit Composite Video Signal with Ethernet data simultaneously.

Specifications

Input:

- 12VDC to 24VDC Class 2 power supply (polarity not observed) or 16VAC to 24VAC Class 2 plug-in transformer.

Power Consumption:

- 12VDC/275mA, 24VDC/110mA,
16VAC/375mA, 24VAC/200mA.

sloc[™] Compliant:

- Incorporates *sloc[™] (Security Link over Coax) technology.

Ethernet:

- Connectivity: RJ45, auto-crossover.
- Wire type: 4-pair Cat-5 or higher structured cable.
- Distance: up to 328 ft. (100m).
- Speed: 10/100BaseT, half/full duplex, auto negotiation.
- Throughput is rated to pass 25mbps of data at distances up to 1500 ft. With proper headend equipment, multiple Megapixel cameras can be used.

Coax:

- Distance: up to 1,500 ft.
- Connectivity: BNC, RG-59/U or similar.

LED Indicators:

- Blue LED - Coax link connection.
- Yellow and Green LED (RJ45) IP Link status, 10/100Base-T/active.
- Green LED - Power.

Environmental:

- Operating Temperature:
14°F to 122°F (-10°C to +50°C).
- Storage Temperature:
-22° to 158°F (-30° to +70°C) Storage.
- Humidity: 20 to 85%, non-condensing.

Electrical:

- BTU/Hr.:
- VDC: 1.69 - 4.46 BTU/Hr.
- VAC: 2.46 - 3.07 BTU/Hr.

Accessories:

- Composite video cables (included) - enables simultaneous composite video signal over the same Coax.
- Two (2) power connectors.

Applications:

- Retrofit digital IP cameras in an analog CCTV installation.
- Works with Megapixel, HD720, HD1080 and VGA (SD) cameras.
- Extend Network link distance in an industrial environment.
- Upgrade deployed CCTV Coax to a digital network for Retail, Casinos, Airports, Schools, Hospitals, etc.
- Enables simultaneous transmission of composite and digital IP video.

Mechanical:

- Lightweight molded fiberglass reinforced polyester enclosure is corrosion resistant and does not contain halogens.
- Dimensions (W x L x H approx.):
2.5" (63.5mm) x 3.8" (96.52mm) x 1" (25.4mm)
- Product weight (approx.): 4 oz. (0.11 kg).
- Shipping weight (approx.): 7 oz. (0.17 kg).

Additional eBridge models:

- **eBridge1CR:** Single port ethernet receiver (use with eBridge transceiver).
- **eBridge1CT:** Single port ethernet transceiver (use with eBridge receivers).
- **eBridge1CRT:** Single port ethernet receiver and transceiver kit.
- **eBridge4CR:** Four (4) port ethernet receiver.
- **eBridge16CR:** Sixteen (16) port ethernet receiver.

Agency Approvals



UL/CUL Listed for Information
Technology Equipment (UL 60950-1).



European Conformity



C-Tick Approved - Z1409