

HNC344G2-XD-LU



FEATURES

4MP True WDR Smart Color Turret, Exterior

- 4 Megapixel (2688 x 1520) Resolution
- Full HD 4MP real-time video
- PoE
- Full Color Night View
- H.265

Specifications	
Model Number	HNC344G2-XD/LU
Image Sensor	1/1.8" progressive scan CMOS
Min. illumination	0.0005 Lux @ (F1.0, AGC ON), 0 Lux with white light
Shutter time	1/3s ~ 1/100,000s
Lens	2.8mm, 4mm
Angle adjustment	Pan: 0° ~ 360°, tilt 0° ~ 75°, Rotation: 0 ~ 360°
Digital noise reduction	3D DNR
Wide dynamic range	True WDR 120dB
Day & night	24/7 Color
Video compression	Main stream: H.265/H.264/H.265+/H.264+ Sub-stream: H.265/H.264/MJPEG
Triple stream	NO
Audio In	Yes (built in mic)
Alarm	N/A

Specifications	
Max. image resolution	2688×1520
Frame rate	60 Hz: 30 fps (2688 × 1520, 1920 × 1080, 1280 × 720)
Image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser
BLC	Yes
On Board Storage	Micro SD slot, up to 128GB
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
API	ONVIF(Profile S, Profile G), ISAPI
General functionalities	User authentication, watermark
Communication interface	1 RJ45 10M / 100M Ethernet interface
Operating conditions	-30°C ~ 60°C (-22°F ~ 140°F) humidity 95% or less (non-condensing)
Power supply	12 VDC +/- 25%, PoE (802.3af, class 3)
Power consumption	Max, 7.6W
Ratings	IP66
Visible Light Range	Up to 90ft
Dimensions	Ø 138.3 mm × 125.2 mm (Ø 5.4" × 4.9")
Weight	750 g (1.7 lb.)
Electrical Box	HTH-280ZJ-DM21
Wall Mount	HTH-273ZJ-140B
Pendant	HTH-271ZJ-140
Corner and Pole	C:HTH-276ZJ, P:HTH-275ZJ