

# HNC344-XB-L-SP



## FEATURES

4MP True WDR Solar Powered Smart Color Bullet, Exterior

- 4 Megapixel (2688 x 1520) Resolution
- Solar Powered
- Full Color Night View
- H.265
- Micro SD Sim Card
- Strobe Light With Audible Alarm
- Built In Mic and Speaker

Specifications	
Model Number	HNC344-XBLSP/4
Image Sensor	1/1.8" Progressive Scan CMOS
Min. illumination	0.0005 Lux @ (F1.0, AGC ON), B/W: 0 Lux with white light
Shutter time	1/3s ~ 1/100,000s
Lens	4mm
Angle Adjustment	Solar Cover: Pan: 0° to 358°, tilt: -40° to 40° Camera: Pan: 0° to 360° tilt: -60° to 0°
Digital noise reduction	3D DNR
Wide dynamic range	True WDR 120dB
Day & night	24/7 Color with visible light
Video compression	Main stream: H.265 Sub-stream: H.265/MJPEG *Full power mode: main stream supports H.265+
Audio	Yes (built in mic)
Alarm	Audible Warning and Strobe Light

<b>Specifications</b>	
Max. image resolution	2688 × 1520
Frame rate	50 Hz: 12.5 fps (2688 × 1520, 1920 × 1080, 1280 × 720) 60 Hz: 15 fps (2688 × 1520, 1920 × 1080, 1280 × 720)
Image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser
Sim Card	Yes. Micro SD SIM. T-Mobile hotspot SIM suggested.
On Board Storage	64GB, Micro SD slot, up to 256GB
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
API	ONVIF(Profile S, Profile G), ISAPI
General functionalities	User authentication, watermark
Communication interface	1 RJ45 10M / 100M Ethernet interface
Operating conditions	-20 °C to 60 °C (-4 °F to 131 °F). Humidity 95% or less (non-condensing)
Power supply	12 VDC ± 20%, Ø5.5 mm coaxial power plug
Power consumption	Max, 7.2W
Ratings	IP67
Visible Light Range	Up to 90ft
Dimensions	614.8 mm × 390.5 mm × 760 mm (24.2" × 15.4" × 29.9")
Weight	Pre-install plate: approx. 1080 g (2.4 lb.) Bullet camera + bracket + solar panel: approx. 8540 g (18.8 lb.)
Electrical Box	N/A
Wall Mount	N/A
Pendant	N/A
Corner and Pole	N/A