

HNC348G2-XBL - Hunt Electronic

huntcctv.com/product/hnc348g2-xbl





Specifications

Model Number	HNC348G2-XBL
Image Sensor	1/1.2" progressive scan CMOS
Min. illumination	0.0005 lux @ (F1.0, AGC ON)
Shutter time	1/3s ~ 1/100,000s
Lens	4mm (2.8 mm optional)
Angle adjustment	Pan: 0° ~ 360°, tilt 0° ~ 90°, Rotation: 0 ~ 360°
Digital noise reduction	3D DNR

Specifications

Wide dynamic range	True WDR 120dB
Day & night	24/7 Color with visible light
Video compression	H.264 / H.264+ / MJPEG / H.265 / H.265+
Triple stream	Yes
Audio	N/A
Alarm	N/A
Max. image resolution	3840 x 2160
Frame rate	24 FPS @ 3840 x 2160
Image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser
BLC	Yes
On Board Storage	Micro SD slot, up to 256GB
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
API	ONVIF(Profile S, Profile G), ISAPI
General functionalities	User authentication, watermark
Communication interface	1 RJ45 10M / 100M Ethernet interface
Operating conditions	-30°C ~ 60°C (-22°F ~ 140°F) humidity 95% or less (non-condensing)
Power supply	12 VDC +/- 10%, PoE (802.3af, class 3)
Power consumption	Max, 9.5W
Ratings	IP67
Visible Light Range	Up to 90ft
Dimensions	Ø 4.1"x11.4"
Weight	2.6 lbs

Specifications

Electrical Box	HTH-260ZJ
Wall Mount	N/A
Pendant	N/A
Corner and Pole	C:HTH-276ZJ, P:HTH-275ZJ