

HNC348G2-XDLU



FEATURES

8MP True WDR Smart Color Turret, Exterior

- 8 Megapixel (3840 x 2160) Resolution
- Full HD 4MP real-time video
- PoE
- Full Color Night View
- H.265
- Face Capture
- Third Stream

Specifications	
Model Number	HNC348G2-XDLU
Image Sensor	1/1.2" progressive scan CMOS
Min. illumination	0.0005 lux
Shutter time	1/3s ~ 1/100,000s
Lens	4mm (2.8mm optional)
Angle adjustment	Pan: 0° ~ 360°, tilt 0° ~ 75°, Rotation: 0 ~ 360°
Digital noise reduction	3D DNR
Wide dynamic range	True WDR 120dB
Day & night	24/7 Color
Video compression	H.264 / H.264+ / MJPEG / H.265 / H.265+
Triple stream	10FPS @ 1920 x 1080
Audio In	Yes (built in mic)

Specifications	
Alarm	N/A
Max. image resolution	3840 x 2160
Frame rate	24fps (3840×2160)
Image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser
BLC	Yes
On Board Storage	Micro SD slot, up to 256GB
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
API	ONVIF(Profile S, Profile G), ISAPI
General functionalities	User authentication, watermark
Communication interface	1 RJ45 10M / 100M Ethernet interface
Operating conditions	-30°C ~ 60°C (-22°F ~ 140°F) humidity 95% or less (non-condensing)
Power supply	12 VDC +/- 10%, PoE (802.3af, class 3)
Power consumption	Max, 6W
Ratings	IP67
Visible Light Range	Up to 90ft
Dimensions	Ø 5.4"x4.7"
Weight	1.9 lbs
Electrical Box	HTH-280ZJ-DM21
Wall Mount	HTH-273ZJ-140B
Pendant	HTH-271ZJ-140
Corner and Pole	C:HTH-276ZJ, P:HTH-275ZJ