

HNRT10-128/S24R - Hunt Electronic

huntcctv.com/product/hnrt10-128-s24r





Specifications

Model Number	HNRT10-128/S24R
Video Compression	H.265, H.264+, H.264, MPEG4, MJPEG (Hunt IP Cameras Only)
IP Video Input	128 Ch. 1280 Mbps max input (with RAID on, 640)
Video Output	4 HDMI, 2 VGA
RAID	0, 1, 5, 6, 10

Specifications

Audio Input/Output	1/2
Two-way Audio	1/1
Decoding Capability	2-ch@32 MP (30 fps)/2-ch@24 MP (30fps)/4-ch@16 MP (30fps)/8-ch@8 MP (30fps)/16-ch@4 MP (30fps)/32-ch@2 MP (30fps)
HDMI Output Resolution	Max 8K resolution 7860 x 4320@ 30Hz
VGA Output Resolution	1080P,60Hz
Synchronous Playback	16 Ch.
Network Interface	4 RJ45 10M/100M/1000M, 2 SFP 1000 Mbps Optical Port
PoE Network Interfaces/Built-in switch	N/A
Internal SATA	24 SATA, 3.5 inch HDD
Alarm In/out	32/16
eSATA	1 eSATA
USB interface	2 x USB2.0, 4 x USB3.0
Operation Temperature	-10 to 55°C (14 to 131° F)
Obtained Certification	CE, IC, CB, Rohs, Reach, WEEE, RCM, UKCA, LOA
Dimension	447 mm × 572 mm × 173 mm (17.6 × 22.5 × 6.8 inch)
Power Supply	100 to 240 VAC, 50 to 60 Hz, redundant power supply
Weight	≤ 19 kg (without HDD, 28.7 lb.)