

READY TO SHIP:

- Immediate Nationwide Inventory Availability
- Delivery Nationwide within One Week



**Rapid Return
On Investment**



**Customizable
Security Solutions**



**Cost Effective
Application**



**Turnkey
Solution**

PRODUCT SPECIFICATIONS

SOLAR SYSTEM	
Solar Panel	Mono-Crystalline Silicon
Rate Power	435 W x 2
Efficiency	20.3%
LIFTING SYSTEM	
Type	Telescopic Mast
Material	Mast Steel Q235
Max Height	24 ft
Lifting System	Manual
Wind Rating Speed	62 m/h
TRAILER SYSTEM	
Type	Mobile Single Axle Trailer
Tow Hitch	50 mm Ball 4400 lbs
Stabilization Leg	4 pcs Manual
Suspension System	Spring Type
Transportation	Truck, Crane, Forklift
Tire & Rim	185R14C
SPRING CABLE	
Network Cable	CAT6 x 2
Power Cable	2x AWG16+2 x AWG13 / 1x AC Charging Cable (L=2M)

SIZE MEASUREMENTS	
Size	6.2 ft x 5.0 ft x 3.5 ft (Shipping)
	9.5 ft x 5.0 ft x 8.0 ft (Transporting)
	9.5 ft x 8.0 ft x 24 ft (Operating)
BATTERY SYSTEM	
Type	Gel-Battery
Capacity	12 V 200 AH x 4 pcs
Ambient Temperature	-35 C° ~ 60 C°
CHARGE SYSTEM	
Type	MPPT
Rated Charge Current	40 A
Efficiency	99.5%
Charging Time	8.8 H
System Voltage	24 V DC
DC Output	DC 12 V 240 W / DC 24 V 240 W / DC 48 V 480 W
Battery Charger	Use AC power charge battery 1.5 KW

PRODUCT DIMENSIONS

