



# HAC303-FB4



## FEATURES

Twin Turbo HD720P EXIR Bullet Camera

- Full HD720P video output
- HDTVI Technology
- True Day/Night
- EXIR technology, 120 ft IR distance
- IP66 weatherproof
- Up the Coax (control over coax)

Specifications	
Model Number	HAC303-FB4
Image Sensor:	1/3" Progressive Scan CMOS
Signal System	PAL / NTSC
Effective Pixels	1280(H)*720(V)
Min. Illumination:	0.01 Lux @(F1.2,AGC ON), 0 Lux with IR
Shutter speed	1/25(1/30) s to 1/50,000 s
Lens	3.6mm (6mm, 8mm optional) Angle of View: 76.88° (3.6mm), 50.1° (6mm), 36.8° (8mm)
Lens Mount	M12
Day& Night:	IR cut filter with auto switch
Synchronization:	Internal Synchronization
Video Frame Rate	25 fps (PAL) / 30 fps (NTSC)
HD Video Output:	1 Analog HD output
S / N Ratio	More than 52dB

Specifications	
Up the Coax:	Support
Working Temperature / Humidity	-40 °C - 60 °C (-40 °F - 140 °F) Humidity 90% or less (non-condensing)
Power Supply:	12 V DC±10%
Power Consumption:	Max. 4.5W
Weather Proof:	IP66
IR Range	Up to 120 ft
Dimensions	94.6×83×210.8mm(3.72"×3.27"×8.30")
Weight	700 g (1.54 lbs)
Electrical Box	HTH-280ZJ-XS
Pole Mount	HTH-275ZJ
Corner Mount	HTH-276ZJ