



HAC306D-VB4Z



FEATURES

IVMS HD-TVI 5MP Turbo HD Outdoor Motorized Vari-focal EXIR Bullet Camera

- HD 5MP Video Output
- HDTVI Technology
- True Day/Night
- 2.8 - 12mm vari-focal lens
- Motorized Vari-Focal Lens
- EXIR
- OSD menu, 3D DNR, Smart IR
- Up to 120ft IR distance
- DWDR

Specifications	
Model Number	HAC306D-VB4Z
Image Sensor	5MP CMOS
Video Format	PAL / NTSC
Effective Pixels	2560(H)*1944(V)
Min. Illumination	0.008 Lux @ (F1.2,AGC ON),0 Lux with IR
Shutter speed	1/30 s to 1/50,000 s
Lens	2.8-12mm @ F1.2 Motorized, Angle of view: 102° - 31°
Day & Night	ICR
Wide dynamic range	DWDR
Synchronization	Internal synchronization
Video Frame Rate	2560*1944@20fps

Specifications	
HD Video Output	1 Analog HD output
CVBS Output	No
AGC	Support
D/N Mode	Color/BW/Smart
White Balance	ATW, MWB
BLC	Support
Working Temperature / Humidity	-40 °C - 60 °C (-40 °F - 140 °F) Humidity 90% or less (non-condensing)
Power Supply	12 VDC, 24 VAC
Power Consumption	Max. 9W
Weather Proof Ratings	IP67
IR Range	Up to 120 ft
Communication	Up the coax(need UTC controller) Protocol: Pelco-C(Coaxitron)
Dimensions	3.62" x 3.34" x 10.60"
Weight	700 g (1.98 lbs)
Electrical Box	HTH-280ZJ-S
Pole Mount	HTH-275ZJ
Corner Mount	HTH-276ZJ