

HAC318-FD4-2-8



FEATURES

IVMS 4-in-1 8MP Turbo HD Outdoor Turret Camera

- 8MP Video Output
- 4-in-1 Video Output (TVI, CVI, AHD, CVBS)
- True Day/Night
- OSD menu, 3D DNR, Smart IR
- Up to 180ft IR distance
- Up the Coax(via coaxial cable)

| Specifications | |
|--------------------|--|
| Model Number | HAC318-FD4/2.8 |
| Image Sensor | 8.29MP CMOS Sensor |
| Video Format | PAL / NTSC |
| Max resolution | 3840 x 2160 |
| Min. Illumination | 0.01 Lux @ (F1.2,AGC ON),0 Lux with IR |
| Shutter speed | 1/15 s to 1/50,000 s |
| Lens | 2.8mm |
| Day & Night | ICR |
| Synchronization | Internal synchronization |
| Video Frame Rate | TVI: 15FPS @ 8MP, 20FPS @ 5MP, 30FPS @ 4MP CVI: 15FPS @ 8MP AHD: 20FPS @ 5MP |
| HD Video Output | 1 Analog HD output |
| Wide Dynamic Range | 105dB |
| S / N Ratio | More than 52dB |

| Specifications | |
|--------------------------------|---|
| Scene | Indoor, Outdoor, Indoor1, LOW-LIGHT |
| Camera ID | On/off (15 characters, position programmable) |
| AGC | Support |
| D/N Mode | Color/BW/EXT |
| White Balance | ATW, AWC-SET, Indoor, Outdoor, Manua |
| Privacy Mask | On/Off, maximum 2 zones |
| Motion Detection | On/Off, maximum 4 zones |
| BLC | Support |
| Anti-flicker | On/off |
| Language | English, Japanese, CHN1, CHN2, Korean, German, French, Italian, Spanish, Polish, Russian, Portuguese, Dutch, Turkish, Hebrew and Arabic |
| Function | Eclipse, Digital noise reduction, Digital zoom(62x), Slow shutter, Mirror, Defog, Defect pixel correction, SMART D-ZOOM |
| Working Temperature / Humidity | -40 °C - 60 °C (-40 °F - 140 °F) Humidity 90% or less (non-condensing) |
| Power Supply | 12 VDC |
| Power Consumption | 12V DC: Max. 5.3W |
| Weather Proof Ratings | IP67, IK10 |
| IR Range | Up to 180 ft |
| Communication | Up the coax(need UTC controller) Protocol: Pelco-C(Coaxitron) |
| Dimensions | Φ4.32 x 3.6" |
| Weight | 0.71 lb |
| Electrical Box | HTH-285ZJ-M(B) |
| Wall Mount | HTH-272ZJ-110-TRS |
| Pole Mount | HTH-275ZJ |
| Corner Mount | HTH-276ZJ |