



HAR526-8



FEATURES

HD-TVI 8MP 8 Ch Hybrid DVR

- H.265 & Dual-stream video compression
- Support up to 10 IP Cameras, up to 8 MP
- Disable TVI in order to add more IP
- Support HD-TVI, analog, AHD, and HD-CVI cameras with adaptive access
- Full channel@1080P resolution real-time recording
- HDMI and VGA output at up to 4K resolution
- Long transmission distance over coax cable
- Support up to 8-ch synchronous playback at 1080P resolution

Specifications	
Model Number	HAR526-8
Video compression	H.265+ / H.265 / H.264+ / H.264
Analog and HD-TVI video input	8-ch BNC interface (1.0Vp-p, 75 Ω)
IP Video Input	2 Channel (up to 10 channel) up to 8MP (200 Mbps Max input)
Supported camera types	TVI up to 8MP, AHD up to 1080p, CVI up to 1080p, IP up to 8MP
Audio compression	G.711u
Audio input	4-ch, RCA (2.0 Vp-p, 1 KΩ)
Audio output	2-ch, RCA (Linear, 1KΩ, for VGA output and CVBS output respectively)
Audio bitrate	64 Kbps
Two-way audio in	1-ch, RCA (2.0 Vp-p, 1 KΩ)

Specifications	
HDMI1 / VGA output	1920 × 1080 / 60 Hz ,1280 × 1024 / 60 Hz, 1280 × 720 / 60 Hz, 1024 × 768 / 60 Hz
HDMI2	4K (3840 x 2160)30Hz / 2K (2560 x 1440)60Hz / 1920 × 1080 / 60 Hz ,1280 × 1024 / 60 Hz, 1280 × 720 / 60 Hz, 1024 × 768 / 60 Hz
CVBS output	1-ch, BNC (1.0 Vp-p, 75 Ω), resolution: PAL: 704 × 576, NTSC: 704 × 480
Encoding resolution	Main stream: 8MP@8fps; 5 MP@12fps; 4 MP@ 15fps; 3 MP@18fps; 1080p/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N)
Video bitrate	32 Kbps-10 Mbps
Dual-stream	Support
Stream type	Video & Audio
Synchronous playback	8-ch
Remote Connections	128 streams
Network protocols	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF, SNMP
Type	4 SATA interfaces for 4 HDDs; 1 eSATA interface
Capacity	Up to 8 TB capacity for each disk
Disk Array Type	RAID 0, RAID 1, RAID 5, RAID 6, RAID 10
Network interface	2; 10M / 100M / 1000M self-adaptive Ethernet interface
Serial interface	RS-232, RS-485, Keyboard
USB port	2 × USB2.0, 1 x USB3.0
Alarm in / out	16 / 4
Power supply	100 ~ 240VAC, 47 ~ 63HZ
Consumption (without hard disks)	≤ 45W
Working temperature	-10 °C ~+55 °C (14 °F ~ 131 °F)
Working humidity	10% ~ 90%
Chassis	19-inch rack-mounted 1.5U chassis
Dimensions (W × D × H)	445 × 390 × 70 mm (17.5 × 15.3 × 2.7 inch)
Weight (Without disks)	11 lbs