



Analog

BOX

HCB-6001

1080p Analog HD camera



Key Features

- Full HD(1920 x 1080, 30fps) resolution
- 0.09Lux@F1.2(Color), 0.009Lux@F1.2(B/W)
- Day & Night(ICR), WDR(120dB)
- SSNRIV, Motion detection
- Transmission distance max.500m
- Easy installation (Plug & play), Dual power, RS-485

Compatible Devices



SHB-4200H



SHB-4200



SHB-4301HP



STB-4150V



SHB-4300H1

HCB-6001

1080p Analog HD camera



Specifications

Video

Imaging Device	Size	1/2.8"
	Type	CMOS
Resolution		1920x1080
Max. Framerate(NTSC/PAL)		30fps/25fps
Min. Illumination	Color(1/30sec, 30IRE)	0.09
	BW(1/30sec, 30IRE)	0.009
Video Out		BNC: AHD/TVI/CVI/CVBS Selectable
Video Transmission Distance		500m(5C2V Coaxial Cable), 300m(5C2V Coaxial Cable)

Lens

Focus Control	Simple focus, Manual
Lens Type	DC auto iris(IR corrected)
Mount Type	C mount, CS mount

Operational

Day & Night	Auto(ICR)
Backlight Compensation	BLC, HLC, WDR
Wide Dynamic Range (dB)	120
Digital Noise Reduction	SSNRIV
Defog	Support
Motion Detection	Quantity: 4ea
Privacy Masking	Quantity: 4ea
	Shape: Rectangular zones
Gain Control	Low, Middle, High, Very High
White Balance	ATW, AWC, Manual, Indoor, Outdoor
Electronic Shutter	Speed Range: 1~1/12,000sec
Video Rotation	Flip, Mirror
Serial Interface	RS-485

Operational

Alarm Interface	In/Out	Output 1ea
	Others	External D/N
Alarm Triggers		Analytics
Alarm Events When Alarm Trigger Occurred		Alarm output
Coaxial Protocol		ACP, TCP, CCP, CVBS

Analytics

Analytics Events	Normal	Motion detection
------------------	--------	------------------

Environmental & Electrical

Operating Condition	Temperature	-10°C~+55°C(+14°F~+131°F)
	Humidity	0~90% RH(non-condensing)
Input Voltage		24VAC, 12VDC
Power Consumption	12VDC	Max 6W
	24VAC	Max 6W

Mechanical

Color	Ivory, Black
Material	Aluminum, PC(Polycarbonate)
Product Dimensions	130.9(H)×73.1(V)×67.2(D)mm(5.15×2.88×2.65")
Product Weight	287g(0.63lb)

HCB-6001

HCB-6001

1080p Analog HD camera



CAD

Unit: mm [inch]

