



Analog

Dome

HCV-6070R

1080p Analog HD Vandal-Resistant IR Dome Camera



Key Features

- Full HD resolution
- 0.11 Lux@F1.6 (Color), 0 Lux (B/W : IR LED on)
- 3.2 ~ 10mm (3.1x) V/F lens
- Day & Night (ICR), WDR (120dB)
- SSNRIV, Motion detection
- IR viewable length 30m, IP66, IK10
- Transmission distance max.500m
- Easy Installation (Plug & play), Dual power

Compatible Devices



SBP-300CM



SBV-136B



SBP-300PM



SBP-300KM



SBP-300WM1



SBP-300LM



SBP-137WM1



SBP-390WM2



SBP-300WM



SPB-VAN72



SBP-300B



SHD-1408FW



SBP-301HM5



SBP-300NB

HCV-6070R

1080p Analog HD Vandal-Resistant
IR Dome Camera



Specifications

Video		
Imaging Device	Size	1/2.8"
	Type	CMOS
Resolution		1920x1080
Max. Framerate(NTSC/PAL)		30fps/25fps
Min. Illumination	Color(1/30sec, 30IRE)	0.11
	BW(1/30sec, 30IRE)	0.011
Video Out		BNC: AHD/TVI/CVI/CVBS Selectable
Video Transmission Distance		500m(5C2V Coaxial Cable)
Lens		
Focal Length (mm)		3.2~10
Optical Zoom Ratio		3.1x
Max Aperture Ratio (F number)	Wide	1.6
	Angular Field of View	
	Horizontal	110.2°~32°
	Vertical	55.4°~18°
	Diagonal	128.4°~36.6°
Min. Object Distance		0.5m(1.64ft)
Focus Control		Manual
Lens Type		DC auto iris(IR corrected)
Optional Lens		0.5m(1.64ft)
Pan / Tilt / Rotate		
Pan / Tilt / Rotate Range	Pan	0° ~ 350°
	Tilt	0° ~ 67°
	Rotate	0° ~ 355°
Operational		
Day & Night		Auto(ICR)
Backlight Compensation		BLC, HLC, WDR

Operational

Wide Dynamic Range (dB)		120
Digital Noise Reduction		SSNRIV
Defog		Support
Motion Detection	Quantity	4ea
Privacy Masking	Quantity	8ea
	Shape	Rectangular zones
Gain Control		Low, Middle, High, Very High
White Balance		ATW, AWC, Manual, Indoor
Electronic Shutter	Speed Range	1~1/12,000sec
Video Rotation		Flip, Mirror
Alarm Interface	In/Out	Output 1ea
Alarm Triggers		Analytics
Alarm Events When Alarm Trigger Occurred		Alarm output
IR Viewable Length		30m(98.43ft)
Coaxial Protocol		ACP, TCP, CCP, CVBS

Analytics

Analytics Events	Normal	Motion detection
------------------	--------	------------------

Environmental & Electrical

Operating Condition	Temperature	-30°C~+55°C(-22°F~+131°F)
	Humidity	0~90% RH(non-condensing)
Input Voltage		24VAC, 12VDC
Power Consumption	12VDC	Max 4.2W
	24VAC	Max 4.2W

Mechanical

Color	Ivory
Material	Aluminum
Product Dimensions	Ø137x106.1mm(5.39x4.18")
Product Weight	715g(1.58 lb)

Certifications & Standards

Environment	IEC 60529 IP66, IEC 62262 IK10
-------------	--------------------------------

HCV-6070R

HCV-6070R

1080p Analog HD Vandal-Resistant
IR Dome Camera

**CAD**

Unit: mm [inch]

