

HDMI® Splitter

HD2SPL2 HDMI 1 to 2 splitter

HD4SPL2 HDMI 1 to 4 splitter

Features

A splitter is ideal in surveillance situations where a single DVR with HDMI capability may need to be viewed at multiple workstations. These are also very popular for digital signage displays where the same message is being shown to multiple stations. A splitter is also an inexpensive way to take a cable or satellite HDMI signal and distribute it to multiple televisions.

- Takes a single HDMI source and divides it into 2 (HD2SPL2) or 4 (HD4SPL2) monitors or televisions
- Supports 3D HDMI signals
- Supports a wide range of PC and HDTV resolutions from VGA to UXGA, and 480i to 1080p, up to 4K
- Supports DTS/Dolby/DTS-HD/Dolby True HD/LPCM7.1/AC3
- Supports HDCP 1.3
- Compatible with HDMI 1.4a

HD2SPL2

front of unit



rear of unit



HD4SPL2

front of unit




rear of unit



Specifications

Operating Temperature.....	5°F – 131°F
Operating Humidity.....	5% – 90% RH (no condensation)
Input Video Signal	1.2Vp-p
Data Transfer Speed Rate.....	10.2 Gbps (max)
Power Supply	5VDC (power supply included)
Dimensions.....	4.7" (L) x 2.4" (W) x 0.7 (H)
Bandwidth.....	10.2 Gbps
Output Resolutions	480i ~ 1080p @ 50/60
	1080p @ 24/50/60
	2160p @ 24/30
	VGA ~ UXGA



- A** HDMI® input from DVR
- B** HDMI® output to monitors

NDAA
COMPLIANT

*Products are in compliance with NDAA Section 889 Part B Guidelines

The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 2/23/22

HDMI®