



HHR315-8



MB-149 效果图

FEATURES

8 Ch. TVI Camera + 8 Ch. IP Camera / Mix and Match, up to total of 16 Ch. IP Camera

- H.264+ video compression
- Up to 3 Megapixels TVI resolution recording
- IP channels up to 4MP IP Cameras
- HDMI / VGA output up to 1080P
- 4/8/16-ch synchronous playback

Specifications	
Model Number	HHR315-8
BNC video input	8 ch TVI/Analog
Video input interface	BNC (1.0 Vp-p, 75 Ω) PAL / NTSC self-adaptive
IP video input	Up to 16 ch (up to 4MP)
Composite video input	Up to 8 ch
Audio input	4 ch, RCA (2.0 Vp-p, 1 K Ω)
Incoming Bandwidth	128 Mbps
HDMI / VGA output	1920 \times 1080 / 60 Hz (1080P) 1600 \times 1200 / 60 Hz 1280 \times 1024 / 60 Hz 1280 \times 720 / 60 Hz 1024 \times 768
CVBS output	1 ch, BNC (1.0 Vp-p, 75 Ω)
Audio output	1 ch, RCA (Linear, 1 K Ω)
Max. remote connection	128 ch
Outgoing bandwidth	240 Mbps

Specifications	
Video compression	H.264 / H.264+
Encoding resolution	Main stream:20FPS @ 4MP(IP only), 15FPS @ 3MP, 30FPS @ 1080P
Video bitrate	32 Kbps ~ 3 Mbps
Audio bitrate	64 Kbps
Stream type	Video, Video & Audio
Alarm I/O	8/4
Playback resolution	3MP/1080p/UXGA/720P/WD1/4CIF/VGA/DCIF/2CIF/CIF/QCIF
Synchronous playback	8 ch
Record mode	Manual recording, Continuous recording, Motion detection recording, Alarm recording, Motion Alarm recording, Motion & Alarm recording
Playback mode	Instant playback, Normal playback, Event playback, Tag playback
Backup mode	Normal backup, Event backup
Protocol	IPv6, HTTPS, UPnP™, SNMP, NTP, SADP, SMTP, NFS, iSCSI, PPPoE, etc.
Type	2 SATA interfaces
Capacity	Up to 8 TB capacity for each disk
Two-way audio	1 ch, RCA (2.0 Vp-p, 1 KΩ) (Using audio input)
Network interface	1, 10M/100/1000M self-adaptive Ethernet interface
Serial interface	1 × USB2.0, 1 x USB3.0
Power supply	12 VDC
Consumption (without hard disk)	Max. 10W
Working temperature	-10 °C ~ +55 °C (14 °F ~ 131 °F)
Working humidity	10%~90%
Chassis	380 1U chassis
Dimensions (W×D×H)	14.9 "× 12.6" × 1.89"inch
Weight	6.6 Lbs (without hard disk)