

# HNC303-XB



## Features

3MP EXIR Bullet, Exterior

- 3 Megapixel (2048 x 1536) Resolution
- Full HD 1080p real-time video
- True WDR & 3D DNR & BLC
- EXIR illuminators: up to 150ft.
- IP66
- PoE

Specifications	
Model Number	HNC303-XB
Image Sensor	1/3" progressive scan CMOS
Min. illumination	0.07 lux @ F1.2, AGC ON, 0 lux with IR
Shutter time	1/25s (1/30s) ~ 1/100.000s
Lens	4mm@F2.0. angle of view: 75.8° (6mm optional)
lens mount	M12
Day & night	ICR
Digital noise reduction	3D DNR
Wide Dynamic Range	True WDR, 120db
Backlight compensation	Yes, zone configurable
Video compression	H.264 / MJPEG
H.264 compression profile	Main profile
Bit rate	32 Kbps ~ 16 Mbps
Dual stream	Yes
Max. image resolution	3MP CMOS,(2048 x 1536)
Frame rate	60Hz: 20fps (2048 x 1536), 30fps (1920 x 1080), 30fps (1280 x 720)
Image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser

Specifications	
Network storage	NAS
Alarm trigger	Motion detection, tampering alarm
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
System compatibility	ONVIF, PSIA, CGI
General functionalities	User authentication, watermark
Communication interface	1 RJ45 10M/ 100 M Ethernet interface
Operating conditions	-30 °C ~ 60 °C (-22 °F ~ 140 °F) humidity 90% or less (non-condensing)
Power supply	12 VDC +/- 10%, PoE (802.3af)
Power consumption	Max. 7W
Ingress protection	IP66
EXIR range	up to 150ft.
Dimensions	3.95" x 3.46" x 6.19"
Weight	700g (1.5 lbs)
Electrical Box	HTH-260ZJ
Pole,Corner	P:HTH-275ZJ,C:HTH-276ZJ

[X](#)