



# HNC322-TD



## FEATURES

2MP True WDR IR Dome Camera

- 2 Megapixel High Resolution
- Full HD 2MP Video Output
- Low Illumination
- 3D DNR; True WDR; BLC; True D/N
- IP67 & IK10 Rating
- IR Range: up to 100ft
- H.265

Specifications	
Model Number	HNC322-TD
Image Sensor	1/2.8" progressive scan CMOS
Min. illumination	0.01 lux @ (F1.2, AGC ON), 0 lux with IR
Shutter time	1/3s ~ 1/100,000s
Lens	4mm (2.8mm, 6mm optional)
Day & night	IR cut filter with auto switch
Digital noise reduction	3D DNR
Wide dynamic range	True WDR
Video compression	H.264 / H.264+ / MJPEG / H.265 / H.265+
Max. Image Resolution	1920 x 1080
Frame rate	30fps (1920 x 1080)
Image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser

Specifications	
Storage	NAS, on board 128GB SD card slot.
Alarm trigger	motion detection, tampering alarm, network disconnect, IP address conflict, storage exception
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
Security	User Authentication, reset button, flickerless, dual stream, heartbeat, mirror, watermark
Communication interface	1 RJ45 10M/ 100 M Ethernet interface
Operating conditions	-30 °C ~ 60 °C (-22 °F ~ 140 °F) humidity 90% or less (non-condensing)
Power supply	12 VDC +/- 10%, PoE (802.3af)
Power consumption	Max, 6.5W
Weather proof rating	IP67, IK10
IR range	UP to 100ft
Dimension	Φ4.4" × 3.2"
Weight	1.1lbs
Electrical Box	HTH-280ZJ-DM18
Wall Mount	HTH-272ZJ-110B, HTH-258ZJ
Pendant Mount	HTH-271ZJ-110
Corner Mount	HTH-276ZJ
Pole Mount	HTH-275ZJ