

HNC322-VBZ



FEATURES

2.0 MegaPixel Motorized Vari-Focal Bullet IP Camera

- Up to 2 megapixel (1920 × 1080) resolution
- Standard video compression with high compression ratio
- Progressive scan CMOS, capture motion video without incised margin
- Support dual stream, and the sub-stream for mobile surveillance
- Built-in Micro SD/SDHC/SDXC card slot, up to 128 GB
- IR cut filter with auto switch
- PoE (Power over Ethernet)

Specifications	
Model Number	HNC322-VBZ
Image Sensor	1/2.8" Progressive Scan CMOS
Min. Illumination	0.01Lux @ (F1.2, AGC ON), 0 Lux with IR
Shutter Speed	1/3 s to 1/100,000 s
Lens	2.8 - 12 mm @ F2.0, Angle of view: 99.6° - 35°
Day & Night	IR cut filter with auto switch
Digital Noise	3D DNR
Wide Dynamic Range	120dB
Video Compression	H.264 / H.264+ / H.265 / H.265+ / MJPEG
Composite Video	CVBS Out
Audio Compression	G.711/G.722.1/G.726/MP2L2/PCM
Audio Bit Rate	64Kbps(G.711)/16Kbps(G.722.1)/16Kbps(G.726)/32-192Kbps(MP2L2)
Dual Stream	Yes
Max. Resolution	1920 × 1080
Frame Rate	30fps(1920 × 1080)
Backlight compensation	Yes
Network Storage	NAS
Alarm Trigger	Motion detection, Tampering alarm, Network disconnect, IP address conflict, Storage full , Storage error
Alarm I/O	1/1

Specifications	
Audio I/O	1/1
Security	User Authentication, Watermark
Standard	ONVIF, ISAPI
Communication Interface	1 RJ45 10M/100M Ethernet interface/ Composite Out
On-board storage	Built-in Micro SD/SDHC/SDXC card slot, up to 128 GB
Operating Conditions	-30 °C - 60 °C (-22 °F - 140 °F) Humidity 95% or less (non-condensing)
Power Supply	12 V DC ± 25% PoE (802.3af)
Power Consumption	Max. 12.9 W
Ingress Protection level	IP67
IR Range	100ft.
Dimensions	Φ 4.1" × 11.6"
Weight	2.3 lbs
Electrical Box	HTH-260ZJ
Pole,Corner	P:HTH-275ZJ,C:HTH-276ZJ