



HNC322-VDZ



FEATURES

2MP IR Dome, Exterior

- Up to 2 megapixel (1920 × 1080) resolution, real-time output
- Standard video compression with high compression ratio
- Progressive scan CMOS, capture motion video without incised margin
- Support dual stream, and sub-stream for mobile surveillance
- Built-in Micro SD/SDHC/SDXC card slot, up to 128 GB
- IR cut filter with auto switch
- PoE (Power over Ethernet)
- IP67 & IK10

Specifications	
Model Number	HNC322-VDZ
Image Sensor	1/2.8" Progressive Scan CMOS
Min. Illumination	0.01lux @(F1.2,AGC ON) ,0 Lux with IR
Shutter Speed	1/3 s to 1/100,000 s
Lens	2.8 - 12 mm @ F1.4,Angle of view: 99.6°-35°
Angle Adjustment	Pan: 0° - 355°, Tilt: 0° - 75°, Rotation: 0° - 355°
Day &Night	IR cut filter with auto switch
Digital Noise Reduction	3D DNR
Wide Dynamic Range	120dB
Video Compression	H.264 / H.264+ / H.265 / H.265+ / MJPEG
Video Bit Rate	32 Kbps - 8 Mbps
Audio Compression	G.711/G.722.1/G.726/MP2L2/PCM
Audio	1/1
Dual Stream	Yes
Max. Resolution	1920 × 1080

Specifications	
Frame Rate	30fps(1920 × 1080)
Backlight compensation	Yes
Network Storage	NAS
Alarm	1/1
Protocols	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,PPPoE,NTP,UPnP,SMTP,SNMP,IGMP,802.1X,QoS,IPv6,Bonjour
Security	User Authentication, Watermark
Standard	ONVIF, ISAPI
Communication Interface	1 RJ45 10M/100M Ethernet interface
On-board storage	Built-in Micro SD/SDHC/SDXC card slot, up to 128 GB
Operating Conditions	-30 °C - 60 °C (-22 °F - 140 °F) Humidity 95% or less (non-condensing)
Power Supply	12 V DC ± 25% PoE (802.3af)
Power Consumption	Max. 12W
Ingress Protection level	IP67
Impact Protection	IK10
IR Range	up to 100ft.
Dimensions	Φ 140 × 99.9 mm (Φ 6" × 4.4")
Weight	1.9lbs
Electrical Box	HTH-280ZJ-DM21
Wall Mount	HTH-273ZJ-135B
Recess Mount	HTH-227ZJ-DM37
Corner and Pole	C:HTH-276ZJ, P:HTH-275ZJ