

HNC324G2-TD - Hunt Electronic

 huntcctv.com/product/hnc324g2-td





Specifications

Model Number	HNC324G2-TD
Image Sensor	1/3" progressive scan CMOS
Min. illumination	0.005 Lux @ (F1.6, AGC ON), 0 Lux with IR on
Shutter time	1/3s ~ 1/100,000s
Lens	4mm @ F1.6, 2.8mm optional
Angle adjustment	Pan: -90° ~ 90°, tilt 0° ~ 75°, Rotation: 0-355°
Digital noise reduction	3D DNR

Specifications

Wide dynamic range	True WDR
Day & night	ICR
Video compression	Main stream: H.265/H.264/H.264+/H.265+ Sub-stream: H.265/H.264/MJPEGThird-stream: H.265/H.264/H.264+/H.265+ (Third Stream must have VCA functions turned off)
Triple stream	Yes
Audio	N/A
Alarm	N/A
Max. image resolution	2688×1520
Frame rate	60 Hz: 30 fps (2688 × 1520, 1920 × 1080, 1280 × 720)
Image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser
BLC	Yes, zone configurable
On Board Storage	Micro SD slot, up to 128GB
Alarm trigger	Motion detection, tampering alarm
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
System compatibility	ONVIF, CGI
General functionalities	User authentication, watermark
Communication interface	1 RJ45 10M / 100M Ethernet interface
Operating conditions	-30°C ~ 60°C (-22°F ~ 140°F) humidity 90% or less (non-condensing)
Power supply	12 VDC +/- 25%, PoE (802.3af)
Power consumption	Max, 6.5W

Specifications

Ratings	IP67 / IK10
IR range	Up to 90ft
Dimensions	Ø 110.8 × 84.7 mm (Ø4.4" × 3.3")
Weight	530 g (1.2 lb.)
Electrical Box	HTH-280ZJ-DM18
Wall Mount	HTH-258ZJ, HTH-272ZJ-110B
Pendant	HTH-271ZJ-110
Corner and Pole	C:HTH-276ZJ, P:HTH-275ZJ