



# HNC326-TD



## FEATURES

6MP True WDR Fixed Mini Dome, Exterior

- 6 Megapixel (3072 x 2048) Resolution
- 3D DNR, 120dB WDR, BLC
- IP67 & IK10 Rating
- 12 VDC & PoE (802.3af)
- Vandal-proof

Specifications	
Model Number	HNC326-TD
Image Sensor	1/2.9" progressive scan CMOS
Min. illumination	0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR
Shutter time	1/3s ~ 1/100,000s
Lens	4mm @ F1.2, angle of view: 63.5° (2.8, 6mm optional)
Angle adjustment	Pan:0° ~ 355°, tilt 0° ~ 75°, Rotation: 0°~ 355°
Digital noise reduction	3D DNR
Wide dynamic range	True WDR
Day & night	ICR
Video compression	H.264 / H.264+ / H.265 / H.265+ / MJPEG
Dual stream	Yes
Max. image resolution	3072×2048
Frame rate	20fps(3072×2048), 30fps(2560×1440)

Specifications	
Image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser
BLC	Yes, zone configurable
On Board Storage	Micro SD slot, up to 128GB
Alarm trigger	Motion detection, tampering alarm
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
System compatibility	ONVIF(PROFILE S, PROFILE G), PSIA, CGI, ISAPI
General functionalities	One-key Reset, Anti-Flicker, Heartbeat, Mirror, Password Protection, Privacy Mask, Watermark, IP Address Filter
Communication interface	1 RJ45 10M / 100M self-adaptive Ethernet interface
Operating conditions	-30°C ~ 60°C (-22°F ~ 140°F) humidity 95% or less (non-condensing)
Power supply	12 VDC +/- 25%, PoE (802.3af)
Power consumption	12 VDC, 6.2W; PoE(802.3af, class 3), 9 W
Ratings	IP67 / IK10
IR range	Up to 100ft
Dimensions	Ø 4.4"x3.2"
Weight	500g (1.1 lbs)
Electrical Box	HTH-280ZJ-DM18
Wall Mount	HTH-258ZJ, HTH-272ZJ-110B
Pendant	HTH-271ZJ-110
Corner and Pole	C:HTH-276ZJ, P:HTH-275ZJ