



HNC328MB



FEATURES

8MP True WDR IR Mini Bullet Camera

- 8 Megapixel High Resolution
- Full HD Video Output
- Low Illumination
- 3D DNR; True WDR; BLC
- IP67 Rating
- IR Range: up to 100ft
- True Day / Night

Specifications	
Model Number	HNC328-MB
Image Sensor	1/2.5" progressive scan CMOS
Min. illumination	0.01 lux @ (F1.2, AGC ON), 0 lux with IR
Shutter time	1/3s ~ 1/100,000s
Lens	4mm @ F2.0 Angle of view: 102° / Optional 2.8mm, 6mm
Day & night	IR cut filter with auto switch
Digital noise reduction	3D DNR
Wide dynamic range	True WDR
Video compression	H.265 /H.264+/H.264/ MJPEG
Max. Image Resolution	3840×2160
Frame rate	15fps (3840×2160), 30fps (2560×1920)
Image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser

Specifications	
storage	NAS, on board 128GB SD card slot
Alarm trigger	motion detection, tampering alarm, network disconnect, IP address conflict, storage exception
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
Security	User Authentication, reset button, flickerless, dual stream, heartbeat, mirror, watermark
Communication interface	1 RJ45 10M/ 100 M Ethernet interface
Operating conditions	-30 °C ~ 60 °C (-22 °F ~ 140 °F) humidity 90% or less (non-condensing)
Power supply	12 VDC +/- 10%, PoE (802.3af)
Power consumption	Max, 7W
Weather proof rating	IP67
IR range	UP to 100ft
Dimension	Φ2.76" × 6.1"
Weight	0.9lbs
Electrical Box	HTH-280ZJ-XS