



# HNC328XB



## FEATURES

8MP True WDR EXIR Bullet Camera

- 8 Megapixel High Resolution
- Full HD 1080p Video Output
- Low Illumination
- 3D DNR; True WDR; BLC
- IP66 Rating
- IR Range: up to 150ft
- True Day / Night

Specifications	
Model Number	HNC328-XB
Image Sensor	1/2.5" progressive scan CMOS
Min. illumination	0.01 lux @ (F1.2, AGC ON), 0 lux with IR
Shutter time	1/3s ~ 1/100,000s
Lens	2.8mm @ F2.0 Angle of view: 102°
Day & night	IR cut filter with auto switch
Digital noise reduction	3D DNR
Wide Dynamic Range	True WDR
Video compression	H.264 / MJPEG / H.265
Max. Image Resolution	3840×2160
Frame rate	15fps (3840×2160), 30fps (2560×1440)
Image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser

<b>Specifications</b>	
Network storage	NAS
Alarm trigger	motion detection, tampering alarm, network disconnect, IP address conflict, storage exception
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
Security	User Authentication, reset button, flickerless, dual stream, heartbeat, mirror, watermark
Communication interface	1 RJ45 10M/ 100 M Ethernet interface
Operating conditions	-30 °C ~ 60 °C (-22 °F ~ 140 °F) humidity 90% or less (non-condensing)
Power supply	12 VDC +/- 10%, PoE (802.3af)
Power consumption	Max, 12.5W
Weather proof rating	IP66
IR range	UP to 150ft
Dimension	Φ4.13" × 11.8"
Weight	2.65lbs
Electrical Box	HTH-260ZJ