



HNC344-XB



FEATURES

4MP True WDR Smart sense Fixed Bullet, Exterior

- 4 Megapixel (2688 x 1520) Resolution
- Full HD 4MP real-time video
- Smart Sense
- IP67 Rating
- PoE
- EXIR
- H.265

| Specifications | |
|-------------------------|---|
| Model Number | HNC344-XB |
| Image Sensor | 1/2.7" progressive scan CMOS |
| Min. illumination | 0.007 lux @ (F1.2, AGC ON), 0 lux with IR |
| Shutter time | 1/3s ~ 1/100,000s |
| Lens | 2.8mm @ F1.2 |
| Angle adjustment | Pan: 0° ~ 360°, tilt 0° ~ 90°, Rotation: 0 ~ 360° |
| Digital noise reduction | 3D DNR |
| Wide dynamic range | True WDR 120dB |
| Day & night | ICR |
| Video compression | H.264 / H.264+ / MJPEG / H.265 / H.265+ |
| Triple stream | Yes |
| Audio | N/A |
| Alarm | N/A |
| Max. image resolution | 2688×1520 |
| Frame rate | 30fps (2688×1520) |
| Image settings | Saturation, brightness, contrast, sharpness adjustable through client software or web browser |
| BLC | Yes |

| Specifications | |
|-------------------------|--|
| On Board Storage | Micro SD slot, up to 128GB |
| Alarm trigger | Tampering alarm, network disconnected, IP address conflict, illegal login, HDD full, HDD error |
| Protocols | TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos |
| API | ONVIF(Profile S, Profile G), ISAPI |
| General functionalities | User authentication, watermark |
| Communication interface | 1 RJ45 10M / 100M Ethernet interface |
| Operating conditions | -30°C ~ 50°C (-22°F ~ 122°F) humidity 95% or less (non-condensing) |
| Power supply | 12 VDC +/- 10%, PoE (802.3af, class 3) |
| Power consumption | Max, 10.5W |
| Ratings | IP67 |
| IR range | Up to 150ft |
| Dimensions | Ø 4.1"x11.4" |
| Weight | 2.4 lbs |
| Electrical Box | HTH-260ZJ |
| Wall Mount | N/A |
| Pendant | N/A |
| Corner and Pole | C:HTH-276ZJ, P:HTH-275ZJ |