



HNC344-XDLU



FEATURES

4MP True WDR Smart sense Smart Color Turret, Exterior

- 4 Megapixel (2688 x 1520) Resolution
- Full HD 4MP real-time video
- Smart Sense
- PoE
- Full Color Night View
- H.265

| Specifications | |
|-------------------------|---|
| Model Number | HNC344-XDLU |
| Image Sensor | 1/1.8" progressive scan CMOS |
| Min. illumination | 0.0014 lux @ (F1.0, AGC ON), 0 lux with IR |
| Shutter time | 1/3s ~ 1/100,000s |
| Lens | 4mm |
| Angle adjustment | Pan: 0° ~ 360°, tilt 0° ~ 75°, Rotation: 0 ~ 360° |
| Digital noise reduction | 3D DNR |
| Wide dynamic range | True WDR 120dB |
| Day & night | ICR |
| Video compression | H.264 / H.264+ / MJPEG / H.265 / H.265+ |
| Triple stream | Yes |
| Audio | N/A |
| Alarm | N/A |

| Specifications | |
|-------------------------|--|
| Max. image resolution | 2688×1520 |
| Frame rate | 30fps (2688×1520) |
| Image settings | Saturation, brightness, contrast, sharpness adjustable through client software or web browser |
| BLC | Yes |
| On Board Storage | Micro SD slot, up to 128GB |
| Alarm trigger | Tampering alarm, network disconnected, IP address conflict, illegal login, HDD full, HDD error |
| Protocols | TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos |
| API | ONVIF(Profile S, Profile G), ISAPI |
| General functionalities | User authentication, watermark |
| Communication interface | 1 RJ45 10M / 100M Ethernet interface |
| Operating conditions | -30°C ~ 60°C (-22°F ~ 140°F) humidity 95% or less (non-condensing) |
| Power supply | 12 VDC +/- 10%, PoE (802.3af, class 3) |
| Power consumption | Max, 6W |
| Ratings | IP66 |
| Visible Light Range | Up to 90ft |
| Dimensions | Ø 5.4"x5" |
| Weight | 1.3 lbs |
| Electrical Box | HTH-280ZJ-DM21 |
| Wall Mount | HTH-273ZJ-140B |
| Pendant | HTH-271ZJ-140 |
| Corner and Pole | C:HTH-276ZJ, P:HTH-275ZJ |