



HNC-4300H



FEATURES

Touch Screen 4.3" Onvif IP HD 1080p Analogue Camera Tester PTZ UTP

- 4.3 inch Capacitive touch screen , resolution 800(RGB)x 480
- Supports RS 485 PTZ control
- OSD menu
- CVBS/HDMI input
- Measurement POE switch or PSE power supply voltage and cable connection status
- Multi-functional combination interface
- Built-in 7.4V Lithium polymer battery , 5000mAh
- Output one channel PAL/NTSC color bar video signal for testing monitor or video cable.(red, green ,blue, white and black color)
- 12V/2A output

Specifications	
Model Number	HNC-4300H
Screen	4.3 inch Capacitive touch screen , resolution 800(RGB)x 480
Network port	10/100M auto adapt,RJ45
Battery	Built-in 7.4V Lithium polymer battery , 5000mAh
Rechargeable	After charging 7~8 hours, normal working time 16 hours
Video signal test	1 channel Video IN BNC input, 1 channel Video OUT BNC output, support PAL/NTSC
HDMI output	1 channel HDMI output, support 1920 x 1080P
POE Power	48V PoE power output,Max power 24W
12V/2Apower output	Output DC12V/2A power for camera

Specifications	
Charger	DC 12V, 2A
WIFI	Built in WIFI,speeds150M,display wireless camera image
12V output	12V/ 2A
Size	8.35" x 5.34" x 2.23"
Weight	1.65lbs