



# HNC513-ODA



## FEATURES

3MP WDR Motorized VF IR, Vandal-Proof Dome, Exterior

- 3.0 Mega-pixel (2048 x 1536)
- HD 1080p Realtime Video
- 120dB Wide Dynamic Range
- True Day/Night
- 3D Digital Noise Reduction
- Vandal-proof Housing
- IP66 & IK10 Rating
- Up to 150ft IR Range

Specifications	
Model Number	HNC513-ODA
Image Sensor	1/2.8" progressive scan CMOS
Min. illumination	0.014 lux @ F1.2, AGC on, 0 lux with IR
Shutter time	1s ~ 1/100,000s
Lens	2.8 ~ 12mm @ F1.4
Auto Iris	DC drive
Angle Adjustment	Pan: 0° ~ 355°, tilt 0° ~ 75°
Day & Night	IR cut filter with auto switch
Wide Dynamic Range	DWDR, 120dB
Digital noise reduction	3D DNR
Video compression	H.264 / MJPEG/H.264+
Bit rate	32Kbps ~ 16 Mbps

Specifications	
Audio compression	G.711 / G.722.1 / G.726 / MP2L2
Max. image resolution	3MP CMOS,(2048 x 1536)
Frame rate	60Hz: 45fps (2048 x 1536), 60fps (1920 x 1080), 60fps (1280 x 720)
Network storage	NAS
Communication interface	1 RJ45 10M/ 100 M Ethernet interface
Composite out	BNC
Onboard storage	Built-in Micro SD slot, up to 128 GB
Operating conditions	-30 °C ~ 60 °C (-22 °F ~ 140 °F), Humidity 95% or less (non-condensing)
Power supply	DC 12V,AC 24V +/- 10%, PoE (802.3af)
Power consumption	12 W Max
Impact protection	IK10
Weather proof rating	IP66
Dimension	Ø 164.9 x 127 mm(Ø 6.49" x 5")
Weight	2100 g (4.62 lbs)
Wall Mount	HTH-273ZJ-DM26B
Pendant Mount	HTH-268ZJ
Corner and Pole	C:HTH-276ZJ, P:HTH-275ZJ